


**1SS226 (SWITCHING DIODES)****特点/Features :**

速度快，反向恢复时间短；
正向压降低；

印章/ Marking: C3**极限参数/Absolute maximum ratings(Single Diode, Ta=25°C)**

参数/Parameter	符号/ Symbol	数值 /Value	单位 /Unit
Non-Repetitive Peak Reverse Voltage	V_{RM}	85	V
Repetitive Peak Reverse Voltage	V_{RRM}	80	V
Working Peak Reverse Voltage	V_{RWM}		
DC Blocking Voltage	V_R		
Forward Continuous Current	I_{FM}	300	mA
Average Rectified Output Current	I_O	100	mA
Peak Forward Surge Current @t=10mS	I_{FSM}	2	A
Power Dissipation	P_D	150	mW
Junction Temperature	T_j	150	°C
Storage Temperature	T_{stg}	-55~150	°C

电性能参数/Electrical characteristics (Ta=25°C)

参数/Parameter	符号	测试条件	最小值	最大值	单位
Reverse Breakdown Voltage	$V_{(BR)}$	$I_R=100 \mu A$	80		V
Forward Voltage	V_F	$I_F=100mA$		1.2	V
Reverse Voltage Leakage Current	I_R	$V_R=80V$		0.5	μA
Diode Capacitance	C_D	$V_R=0, f=1MHz$		3	pF
Reverse Recovery Time	t_{rr}	$I_F= 10mA$		4	nS



典型特性曲线图/Typical Characteristics

