

everything<sup>®</sup>





# BCM3118B QAMLINK® D

### BCM3118B FEATURES

- Downstream QAM receiver for international applications
- Integrated QAMLink receiver with Forward Error Correction (FEC)
  - 1-7 MBaud variable symbol rate receiver
  - Supports variable channelization
  - Supports 4, 16, 32, 64, 128 and 256-QAM
  - Digital demodulator, Nyquist filters, tracking loops, and 20-tap adaptive decision feedback equalizer
  - Digital derotator for wideband carrier phase tracking
- DVB/DAVIC-compliant FEC decoder
  - Reed-Solomon (N,K) = 204,188: t=8
  - Convolutional detinterleaver, I=1-12 with internal RAM, I=204 with external RAM
- I<sup>2</sup>C or SPI-compatible microcontroller interface
- Integrated 10-bit analog-to-digital converter
- On-chip generation of all clock and control signals
- JTAG test interface
- 100-pin PQFP Package

## **DVB/DAVIC RECEIVER**

#### SUMMARY OF BENEFITS

- Fully integrated solution enables less-complex, low-cost cable modems and cable-TV set-top boxes
- Significantly increases channel capacity
- Variable data rates enable systems to adapt to channels encoded at different data rates
- Integrated A/D converter reduces system manufacturing costs and complexity
- A universal chip solution that supports DVB, DAVIC, ITU-T J.83/Annex A and Annex C, IEEE 802.14-based systems
- Digital adaptive equalizers ensure robust performance in the presence of multipath reflections

#### Interactive Set-Top Box with DOCSIS and Watch and Record Dual Video Channels



#### BCM3118B OVERVIEW



The **BCM3118B** QAMLink DVB/DAVIC Receiver with FEC is an integrated digital transmission solution for cable modems, cable-TV set-top boxes and digital microwave radios. Its bandwidth-efficient feature set expands the existing potential bandwidth of a standard analog network and provides operators with reliable, error-free transmission. Optimized for highvolume manufacturing, the **BCM3118B** is a highly integrated solution that reduces the system-level chip count, the cost, and the complexity associated with manufacturing RF receivers.

A single-chip solution, the **BCM3118B** has a 10-bit A/D converter, a 256-QAM demodulator with square-root raised-cosine receive filters, an adaptive equalizer with an embedded phase recovery derotator, acquisition and tracking loops, and a DVB/DAVIC-compliant Reed-Solomon FEC decoder with deinterleaver. The demodulator supports QPSK, 16, 32, 64, 128 and 256-QAM formats and adapts to channels encoded at different data rates up to 56 Mbps. The equalizer in the **BCM3118B** achieves transmission performance within 1 dB of theory over worse-case channels with multipath delays as long as 2.4 microseconds at 5 MBaud or 1.7 microseconds at 7 MBaud and amplitudes within .5 dB of the desired signals. With this level of performance, the **BCM3118B** combats the effects of channel distortions commonly found in cable-TV systems. The

**Broadcom**\*, the pulse logo, **QAMLink**\* and **Connecting everything**\* are trademarks of Broadcom Corporation and/or its subsidiaries in the United States and certain other countries All other trademarks are the property of their respective owners.



BROADCOM CORPORATION 16215 Alton Parkway, P.O. Box 57013 Irvine, California 92619-7013 © 2003 by BROADCOM CORPORATION. All rights reserved 3118B-PB05-R-06.13.03 **BCM3118B** has an integrated A/D converter, which eliminates the costs associated with fine tuning of external components during high-volume production.

The **BCM3118B** samples the analog IF waveform being delivered to **BCM3118B** by the integrated A/D converter. The signal is then digitally mixed to baseband and filtered by dual square-root Nyquist filters. Inter-symbol interference is then removed by the adaptive decision feedback equalizer. A decision slicer, which supports constellations up to 256-QAM, formats the equalized data. The data is then fed into a DVB/DAVIC-compliant synchronization block, deinterleaver, Reed-Solomon FEC, and derandomizer. The final error-corrected output is delivered in an MPEG-2 transport format.

The **BCM3118B** can be used as a stand-alone chip or with Broadcom's BCM3250 for a complete watch and record solution with EuroDOCSIS. Compliant with the ITU-T J83/Annex A and Annex C, DVB/DAVIC and the IEEE802.14 cable transmission standards for QAM downstream, the **BCM3118B** is a universal downstream solution for worldwide coaxial cable applications.



Phone: 949-450-8700 FAX: 949-450-8710 Email: info@broadcom.com Web: www.broadcom.com