

## isc N-Channel MOSFET Transistor

IPW65R190C7

IIPW65R190C7

## • FEATURES

- Static drain-source on-resistance:  
 $R_{DS(on)} \leq 190m\Omega$
- Enhancement mode:
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

## • DESCRIPTION



- Fast Switching

• ABSOLUTE MAXIMUM RATINGS( $T_a=25^\circ\text{C}$ )

| SYMBOL    | PARAMETER                                  | VALUE    | UNIT             |
|-----------|--------------------------------------------|----------|------------------|
| $V_{DS}$  | Drain-Source Voltage                       | 650      | V                |
| $V_{GS}$  | Gate-Source Voltage                        | $\pm 20$ | V                |
| $I_D$     | Drain Current-Continuous                   | 13       | A                |
| $I_{DM}$  | Drain Current-Single Pulsed                | 49       | A                |
| $P_D$     | Total Dissipation @ $T_c=25^\circ\text{C}$ | 72       | W                |
| $T_j$     | Max. Operating Junction Temperature        | 150      | $^\circ\text{C}$ |
| $T_{stg}$ | Storage Temperature                        | -55~150  | $^\circ\text{C}$ |

## • THERMAL CHARACTERISTICS

| SYMBOL        | PARAMETER                             | MAX  | UNIT               |
|---------------|---------------------------------------|------|--------------------|
| $R_{th(j-c)}$ | Channel-to-case thermal resistance    | 1.73 | $^\circ\text{C/W}$ |
| $R_{th(j-a)}$ | Channel-to-ambient thermal resistance | 62   | $^\circ\text{C/W}$ |



|     | mm    |       |
|-----|-------|-------|
| DIM | MIN   | MAX   |
| A   | 19.80 | 20.20 |
| B   | 15.40 | 15.80 |
| C   | 4.90  | 5.10  |
| D   | 0.90  | 1.10  |
| E   | 1.40  | 1.60  |
| F   | 1.90  | 2.10  |
| G   | 10.80 | 11.00 |
| H   | 2.40  | 2.60  |
| J   | 0.50  | 0.70  |
| K   | 19.50 | 20.50 |
| P   | 3.90  | 4.10  |
| Q   | 3.30  | 3.50  |
| U   | 5.20  | 5.40  |
| V   | 2.90  | 3.10  |

## isc N-Channel MOSFET Transistor

IPW65R190C7

IIPW65R190C7

## ELECTRICAL CHARACTERISTICS

 $T_c=25^{\circ}\text{C}$  unless otherwise specified

| SYMBOL       | PARAMETER                      | CONDITIONS                  | MIN | TYP | MAX | UNIT      |
|--------------|--------------------------------|-----------------------------|-----|-----|-----|-----------|
| $BV_{DSS}$   | Drain-Source Breakdown Voltage | $V_{GS}=0V; I_D=1mA$        | 650 |     |     | V         |
| $V_{GS(th)}$ | Gate Threshold Voltage         | $V_{DS}=V_{GS}; I_D=0.29mA$ | 3   |     | 4   | V         |
| $R_{DS(on)}$ | Drain-Source On-Resistance     | $V_{GS}=10V; I_D=5.7A$      |     |     | 190 | $m\Omega$ |
| $I_{GSS}$    | Gate-Source Leakage Current    | $V_{GS}=20V; V_{DS}=0V$     |     |     | 0.1 | mA        |
| $I_{DSS}$    | Drain-Source Leakage Current   | $V_{DS}=650V; V_{GS}=0V$    |     |     | 1   | $\mu A$   |
| $V_{SD}$     | Diode forward voltage          | $I_F=5.7A, V_{GS}=0V$       |     |     |     | V         |