



Low-Voltage, Quad, SPST CMOS Analog Switches

MAX4610/MAX4611/MAX4612

General Description

The MAX4610/MAX4611/MAX4612 are quad, low-voltage, single-pole/single-throw (SPST) analog switches. On-resistance (100Ω , max) is matched between switches to 4Ω , max and is flat (4Ω , max) over the specified signal range. Each switch handles V₊ to GND analog signal levels. Maximum off-leakage current is only 1nA at T_A = +25°C and 2nA at T_A = +85°C.

The MAX4610 has four normally open (NO) switches, and the MAX4611 has four normally closed (NC) switches. The MAX4612 has two NO switches and two NC switches. These CMOS switches operate from a single +2V to +12V supply. All digital inputs have +0.8V and +2.4V logic thresholds, ensuring TTL/CMOS-logic compatibility when using a single +5V supply.

Applications

- Battery-Operated Equipment
- Audio/Video Signal Routing
- Low-Voltage Data-Acquisition Systems
- Sample-and-Hold Circuits
- Communication Circuits

Features

- ◆ Offered in Automotive Temperature Range (-40°C to +125°C)
- ◆ Guaranteed On-Resistance
100Ω max (5V Supply)
46Ω max (12V Supply)
- ◆ Guaranteed Match Between Channels (4Ω, max)
- ◆ Guaranteed Flatness Over Signal Range (18Ω, max)
- ◆ Off-Leakage Current Over Temperature
<2nA at T_A = +85°C
- ◆ >2kV ESD Protection per Method 3015.7
- ◆ Rail-to-Rail Signal Handling
- ◆ TTL/CMOS-Logic Compatible

Ordering Information


PART	TEMP RANGE	PIN-PACKAGE	PKG CODE
MAX4610CUD	0°C to +70°C	14 TSSOP	U14-1
MAX4610CSD	0°C to +70°C	14 Narrow SO	S14-2
MAX4610CPD	0°C to +70°C	14 Plastic DIP	P14-6
MAX4610C/D	0°C to +70°C	Dice*	—
MAX4610EGER	-40°C to +85°C	16 QFN-EP**	G1644-1
MAX4610EUD	-40°C to +85°C	14 TSSOP	U14-1
MAX4610ESD	-40°C to +85°C	14 Narrow SO	S14-2
MAX4610EPD	-40°C to +85°C	14 Plastic DIP	P14-6
MAX4610ASD	-40°C to +125°C	14 Narrow SO	S14-2

Ordering Information continued at end of data sheet.

*Contact factory for dice specifications.

**EP = Exposed pad.

Pin Configurations/Truth Tables



Low-Voltage, Quad, SPST CMOS Analog Switches

ABSOLUTE MAXIMUM RATINGS

(Voltages referenced to GND.)

V ₊	-0.3V to +13V
IN __ , COM __ , NO __ , NC __ (Note 1)	-0.3V to (V ₊ + 0.3V)
Continuous Current (any terminal) (pulsed at 1ms, 10% duty cycle)	20mA
Peak Current (any terminal) (pulsed at 1ms, 10% duty cycle)	40mA
ESD per Method 3015.7.....	> 2kV

Continuous Power Dissipation (T_A = +70°C)

14-Pin TSSOP (derate 6.3mW/°C above +70°C)	500mW
14-Pin Narrow SO (derate 8.00mW/°C above +70°C) ..	640mW
14-Pin Plastic DIP (derate 10.00mW/°C above +70°C) ..	800mW
16-Pin QFN (derate 18.5mW/°C above +70°C)	1481mW

Operating Temperature Ranges

MAX461_C __	0°C to +70°C
MAX461_E __	-40°C to +85°C
MAX461_A __	-40°C to +125°C

Storage Temperature Range

-65°C to +160°C

Lead Temperature (soldering, 10s)

+300°C

Note 1: Signals on NO_{_}, NC_{_}, COM_{_}, or IN_{_} exceeding V₊ or GND are clamped by internal diodes. Limit forward-diode current to maximum current rating.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS—Single +5V Supply

(V₊ = +5V ±10%, V_{IN_H} = 2.4V, V_{IN_L} = 0.8V, T_A = T_{MIN} to T_{MAX}, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
ANALOG SWITCH						
Analog Signal Range (Note 3)	V _{COM_} , V _{NO_} , V _{NC_}		0	V ₊		V
On-Resistance	R _{ON}	V ₊ = 4.5V, I _{COM_} = 1mA, V _{NO_} = V _{NC_} = 3V	TA = +25°C	70	100	Ω
			TA = T _{MIN} to T _{MAX}		150	
On-Resistance Match Between Channels (Note 4)	ΔR _{ON}	V ₊ = 4.5V, I _{COM_} = 1mA, V _{NO_} = V _{NC_} = 3V	TA = +25°C	1.0	4	Ω
			TA = T _{MIN} to T _{MAX}		8	
On-Resistance Flatness (Note 5)	R _{FLAT(ON)}	V ₊ = 4.5V; I _{COM_} = 1mA; V _{NO_} = V _{NC_} = 3V, 2V, 1V	TA = +25°C	12	18	Ω
			TA = T _{MIN} to T _{MAX}		25	
NO __ or NC __ Off-Leakage Current (Note 6)	I _{NO(OFF)}	V ₊ = 5.5V; V _{COM_} = 1V, 4.5V; V _{NO_} = 4.5V, 1V	TA = +25°C	-0.1	+0.1	nA
			TA = -40°C to +85°C	-2	+2	
			TA = -40°C to +125°C	-30	+30	
COM __ Off-Leakage Current (Note 6)	I _{COM(OFF)}	V ₊ = 5.5V; V _{COM_} = 1V, 4.5V; V _{NO_} = V _{NC_} = 4.5V, 1V	TA = +25°C	-0.1	+0.1	nA
			TA = -40°C to +85°C	-2	+2	
			TA = -40°C to +125°C	-30	+30	
COM __ On-Leakage Current (Note 6)	I _{COM(ON)}	V ₊ = 5.5V; V _{COM_} = 1V, 4.5V; V _{NO_} = V _{NC_} = 1V, 4.5V, or floating	TA = +25°C	-0.2	+0.2	nA
			TA = -40°C to +85°C	-4	+4	
			TA = -40°C to +125°C	-30	+30	

Low-Voltage, Quad, SPST CMOS Analog Switches

ELECTRICAL CHARACTERISTICS—Single +5V Supply (continued)

($V_+ = +5V \pm 10\%$, $V_{IN_H} = 2.4V$, $V_{IN_L} = 0.8V$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP (Note 2)	MAX	UNITS
LOGIC INPUT						
Input Current with Input-Voltage High	I_{IN_H}	$V_{IN_} = 2.4V$, all others = 0.8V	-0.1	± 0.001	+0.1	μA
Input Current with Input-Voltage Low	I_{IN_L}	$V_{IN_} = 0.8V$, all others = 2.4V	-0.1	± 0.001	+0.1	μA
Input High Voltage	V_{IN_H}		2.4	1.5		V
Input Low Voltage	V_{IN_L}			1.4	0.8	V
DYNAMIC (Note 3)						
Turn-On Time	t_{ON}	$V_{COM_} = 3V$, Figure 2	$T_A = +25^\circ C$	35	60	ns
			$T_A = T_{MIN}$ to T_{MAX}		80	
Turn-Off Time	t_{OFF}	$V_{COM_} = 3V$, Figure 2	$T_A = +25^\circ C$	15	20	ns
			$T_A = T_{MIN}$ to T_{MAX}		30	
On-Channel Bandwidth	BW	Signal = 0dBm, Figure 4, 50Ω in and out	$T_A = +25^\circ C$	300		MHz
Charge Injection	V_{CTE}	$C_L = 1.0nF$, $V_{GEN} = 0$, $R_{GEN} = 0$, Figure 3	$T_A = +25^\circ C$	1	5	pC
Off-Isolation (Note 7)	V_{ISO}	$R_L = 50\Omega$, $C_L = 5pF$, $f = 1MHz$, Figure 4	$T_A = +25^\circ C$	-60		dB
Crosstalk (Note 8)	V_{CT}	$R_L = 50\Omega$, $C_L = 5pF$, $f = 1MHz$, Figure 5	$T_A = +25^\circ C$	-80		dB
NO_ or NC_ Capacitance	$C_{(OFF)}$	$f = 1MHz$, Figure 6	$T_A = +25^\circ C$	16		pF
COM_ Off-Capacitance	$C_{COM(OFF)}$	$f = 1MHz$, Figure 6	$T_A = +25^\circ C$	16		pF
COM_ On-Capacitance	$C_{COM(ON)}$	$f = 1MHz$, Figure 6	$T_A = +25^\circ C$	23		pF
Total Harmonic Distortion	THD	600 Ω IN and OUT, 20Hz to 20kHz, 2V _{P-P}	$T_A = +25^\circ C$	0.009		%
SUPPLY						
Power-Supply Range			2	12		V
Supply Current	I_+	$V_{IN} = 0$ or V_+ , all switches on or off	-1	± 0.001	+1	μA

MAX4610/MAX4611/MAX4612

Low-Voltage, Quad, SPST CMOS Analog Switches

ELECTRICAL CHARACTERISTICS—Single +3V Supply

($V_+ = +3V$, $V_{IN_H} = 2.4V$, $V_{IN_L} = 0.5V$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
ANALOG SWITCH						
Analog Signal Range (Note 3)	$V_{COM_}$, $V_{NO_}$, $V_{NC_}$		0		V_+	V
On-Resistance	R_{ON}	$V_+ = 2.7V$, $I_{COM_} = 1mA$, $V_{NO_} = V_{NC_} = 1V$	$T_A = +25^\circ C$	175	360	Ω
			$T_A = T_{MIN}$ to T_{MAX}		450	
On-Resistance Match Between Channels (Note 4)	ΔR_{ON}	$V_+ = 2.7V$, $I_{COM_} = 1mA$, $V_{NO_} = V_{NC_} = 1V$	$T_A = +25^\circ C$	2	5	Ω
			$T_A = T_{MIN}$ to T_{MAX}		10	
NO_ or NC_ Off-Leakage Current (Notes 3, 6)	$I_{NO(OFF)}$	$V_+ = 3.6V$, $V_{COM_} = 0.5V$, 3V; $V_{NO_} = V_{NC_} = 3V$, 0.5V	$T_A = +25^\circ C$	-0.1	+0.1	nA
			$T_A = -40^\circ C$ to $+85^\circ C$	-2	+2	
			$T_A = -40^\circ C$ to $+125^\circ C$	-30	+30	
COM_ Off-Leakage Current (Notes 3, 6)	$I_{COM(OFF)}$	$V_+ = 3.6V$, $V_{COM_} = 0.5V$, 3V; $V_{NO_} = V_{NC_} = 3V$, 0.5V	$T_A = +25^\circ C$	-0.1	+0.1	nA
			$T_A = -40^\circ C$ to $+85^\circ C$	-2	+2	
			$T_A = -40^\circ C$ to $+125^\circ C$	-30	+30	
COM_ On-Leakage Current (Notes 3, 6)	$I_{COM(ON)}$	$V_+ = 3.6V$, $V_{COM_} = 0.5V$, 3V; $V_{NO_} = V_{NC_} = 0.5V$, 3V, or floating	$T_A = +25^\circ C$	-0.2	+0.2	nA
			$T_A = -40^\circ C$ to $+85^\circ C$	-4	+4	
			$T_A = -40^\circ C$ to $+125^\circ C$	-30	+30	
LOGIC INPUTS						
Input High Voltage	V_{IN_H}		2.4	1.0		V
Input Low Voltage	V_{IN_L}			1.0	0.5	V
DYNAMIC (Note 3)						
Turn-On Time	t_{ON}	$V_{COM_} = 1.5V$, Figure 2	$T_A = +25^\circ C$	50	90	ns
			$T_A = -40^\circ C$ to $+85^\circ C$		120	
			$T_A = -40^\circ C$ to $+125^\circ C$		140	
Turn-Off Time	t_{OFF}	$V_{COM_} = 1.5V$, Figure 2	$T_A = +25^\circ C$	30	45	ns
			$T_A = T_{MIN}$ to T_{MAX}		60	

Low-Voltage, Quad, SPST CMOS Analog Switches

ELECTRICAL CHARACTERISTICS—Single +12V Supply

($V_+ = +12V$, $V_{IN_H} = 4V$, $V_{IN_L} = 0.8V$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
ANALOG SWITCH						
Analog Signal Range (Note 3)	$V_{COM_}$, $V_{NO_}$, $V_{NC_}$,		0		V_+	V
On-Resistance	R_{ON}	$V_+ = 12V$, $I_{COM} = 2mA$, $V_{NO_} = V_{NC_} = 10V$	$T_A = +25^\circ C$	30	45	Ω
			$T_A = T_{MIN}$ to T_{MAX}		60	
LOGIC INPUTS						
Input High Voltage	V_{IN_H}		4.0	2.8		V
Input Low Voltage	V_{IN_L}			2.5	0.8	V
SUPPLY						
Positive Supply Current	I_+	$V_{IN_} = 0$ or V_+ , all switches on or off	-1	± 0.001	+1	μA

Note 2: The algebraic convention, where the most negative value is a minimum and the most positive value a maximum, is used in this data sheet.

Note 3: Guaranteed by design.

Note 4: $\Delta R_{ON} = R_{ON}(\text{max}) - R_{ON}(\text{min})$.

Note 5: Flatness is defined as the difference between the maximum and minimum value of on-resistance as measured over the specified analog signal range.

Note 6: Leakage parameters are 100% tested at maximum-rated hot temperature and guaranteed by correlation at $+25^\circ C$.

Note 7: Off-Isolation = $20\log_{10}(V_{COM_}/V_{NO_})$, $V_{COM_}$ = output, $V_{NO_}$ = input to off switch.










Note 8: Between any two switches.

MAX4610/MAX4611/MAX4612

Low-Voltage, Quad, SPST CMOS Analog Switches

Typical Operating Characteristics

($T_A = +25^\circ\text{C}$, unless otherwise noted.)



Low-Voltage, Quad, SPST CMOS Analog Switches

Pin Description

PIN						NAME	FUNCTION		
MAX4610		MAX4611		MAX4612					
TSSOP/SO/DIP	QFN	TSSOP/SO/DIP	QFN	TSSOP/SO/DIP	QFN				
1, 3, 8, 11	1, 3, 8, 11	—	—	—	—	NO1–NO4	Analog Switch Normally Open Terminals		
—	—	1, 3, 8, 11	1, 3, 8, 11	—	—	NC1–NC4	Analog Switch Normally Closed Terminals		
—	—	—	—	1, 8	1, 8	NO1, NO3	Analog Switch Normally Open Terminals		
—	—	—	—	3, 11	3, 11	NC2, NC4	Analog Switch Normally Closed Terminals		
2, 4, 9, 10	2, 4, 9, 10	2, 4, 9, 10	2, 4, 9, 10	2, 4, 9, 10	2, 4, 9, 10	COM1–COM4	Analog Switch Common Terminals		
13, 5, 6, 12	14, 5, 6, 13	13, 5, 6, 12	14, 5, 6, 13	13, 5, 6, 12	14, 5, 6, 13	IN1–IN4	Logic-Control Digital Input		
7	7	7	7	7	7	GND	Ground. Connect to digital ground.		
—	12, 15	—	12, 15	—	12, 15	N.C.	No Connection. Not internally connected.		
14	16	14	16	14	16	V+	Positive Analog and Digital-Supply Voltage Input. Internally connected to substrate.		
—	EP	—	EP	—	EP	EP	Exposed Pad. Connect to V+.		

Applications Information

Power-Supply Sequencing and Overvoltage Protection

Do not exceed the absolute maximum ratings, because stresses beyond the listed ratings may cause permanent damage to the devices.

Proper power-supply sequencing is recommended for all CMOS devices. Always apply V+ before applying analog signals or logic inputs, especially if the analog or logic signals are not current limited. If this sequencing is not possible, and if the analog or logic inputs are not current limited to 20mA, add a small-signal diode (D1) as shown in Figure 1. If the analog signal can dip below GND, add D2. Adding protection diodes reduces the analog signal range to a diode drop (about 0.7V) below V+ (for D1), and to a diode drop above ground (for D2). Leakage is unaffected by adding the diodes. On-resistance increases by a small amount at low supply voltages. Maximum supply voltage (V+) must not exceed 13V.

Adding protection diodes causes the logic thresholds to be shifted relative to the power-supply rails. This can be




Figure 1. Overvoltage Protection Using Two External Blocking Diodes

significant when low supply voltages (+5V or less) are used. With a +5V supply, TTL compatibility is not guaranteed when protection diodes are added. Driving IN1 and IN2 all the way to the supply rails (i.e., to a diode drop higher than the V+ pin, or to a diode drop lower than the GND pin) is always acceptable.

Low-Voltage, Quad, SPST CMOS Analog Switches

Protection diodes D1 and D2 also protect against some overvoltage situations. With Figure 1's circuit, if the supply voltage is below the absolute maximum rating, and if a fault voltage up to the absolute maximum rating is applied to an analog signal pin, no damage will result.

Operating Considerations for High-Voltage Supply

The MAX4610/MAX4611/MAX4612 are pin-compatible with the industry-standard 74HC4066 and the MAX4066, and are optimized for +5V single-supply operation. The MAX4610 family is capable of +12V

single-supply operation with some precautions. The absolute maximum rating for V+ is +13.2V (referenced to GND). When operating near this region, bypass V+ with a minimum 0.1 μ F capacitor to ground as close to the IC as possible.

Caution: The absolute maximum V+ to V- differential voltage is 13.0V. Typical ± 6 V or 12V supplies with $\pm 10\%$ tolerances can be as high as 13.2V. This voltage can damage the MAX4610/MAX4611/MAX4612. Even $\pm 5\%$ tolerance supplies may have overshoot or noise spikes that exceed 13.0V.

Test Circuits/Timing Diagrams




Figure 2. Switching Time




Figure 3. Charge Injection

Low-Voltage, Quad, SPST CMOS Analog Switches

Test Circuits/Timing Diagrams (continued)




Figure 4. Off-Isolation/On-Channel Bandwidth




Figure 5. Crosstalk




Figure 6. Channel Off/On-Capacitance

Ordering Information (continued)


PART	TEMP RANGE	PIN-PACKAGE	PKG CODE
MAX4611CUD	0°C to +70°C	14 TSSOP	U14-1
MAX4611CSD	0°C to +70°C	14 Narrow SO	S14-2
MAX4611CPD	0°C to +70°C	14 Plastic DIP	P14-6
MAX4611C/D	0°C to +70°C	Dice*	—
MAX4611EGE	-40°C to +85°C	16 QFN-EP**	G1644-1
MAX4611EUD	-40°C to +85°C	14 TSSOP	U14-1
MAX4611ESD	-40°C to +85°C	14 Narrow SO	S14-2
MAX4611EPD	-40°C to +85°C	14 Plastic DIP	P14-6
MAX4611AUD	-40°C to +85°C	14 TSSOP	U14-1
MAX4611ASD	-40°C to +85°C	14 Narrow SO	S14-2
MAX4612CUD	0°C to +70°C	14 TSSOP	U14-1
MAX4612 CSD	0°C to +70°C	14 Narrow SO	S14-2
MAX4612CPD	0°C to +70°C	14 Plastic DIP	P14-6
MAX4612C/D	0°C to +70°C	Dice*	—
MAX4612EUD	-40°C to +85°C	14 TSSOP	U14-1
MAX4612ESD	-40°C to +85°C	14 Narrow SO	S14-2
MAX4612EGE	-40°C to +85°C	16 QFN-EP**	G1644-1
MAX4612EPD	-40°C to +85°C	14 Plastic DIP	P14-6
MAX4612AUD	-40°C to +125°C	14 TSSOP	U14-1
MAX4612ASD	-40°C to +125°C	14 Narrow SO	S14-2

*Contact factory for dice specifications.


**EP = Exposed pad.

Low-Voltage, Quad, SPST CMOS Analog Switches


Pin Configurations/Truth Tables (continued)




INPUT	SWITCH STATE
LOW	ON
HIGH	OFF



**EP = EXPOSED PAD, CONNECT EP TO V+



INPUT	N01, N02	NC3, NC4
LOW	OFF	ON
HIGH	ON	OFF




**EP = EXPOSED PAD, CONNECT EP TO V+

Revision History

Pages changed at Rev 4: 1–5, 7, 9, 10, 13.

Low-Voltage, Quad, SPST CMOS Analog Switches

Chip Topographies




TRANSISTOR COUNT: 132

SUBSTRATE CONNECTED TO V+

Package Information



(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information, go to www.maxim-ic.com/packages.)



Low-Voltage, Quad, SPST CMOS Analog Switches

Package Information (continued)


(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information, go to www.maxim-ic.com/packages.)



Low-Voltage, Quad, SPST CMOS Analog Switches

Package Information (continued)

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information, go to www.maxim-ic.com/packages.)



COMMON DIMENSIONS												
PKG	16L 5x5			20L 5x5			28L 5x5			32L 5x5		
	MIN.	NOM.	MAX.									
A	0.80	0.90	1.00	0.80	0.90	1.00	0.80	0.90	1.00	0.80	0.90	1.00
A1	0.00	0.01	0.05	0.00	0.01	0.05	0.00	0.01	0.05	0.00	0.01	0.05
A2	0.00	0.65	1.00	0.00	0.65	1.00	0.00	0.65	1.00	0.00	0.65	1.00
A3	0.20 REF											
b	0.28	0.33	0.40	0.23	0.28	0.35	0.18	0.23	0.30	0.18	0.23	0.30
D	4.90	5.00	5.10	4.90	5.00	5.10	4.90	5.00	5.10	4.90	5.00	5.10
D1	4.75	BSC										
E	4.90	5.00	5.10	4.90	5.00	5.10	4.90	5.00	5.10	4.90	5.00	5.10
E1	4.75	BSC										
e	0.80	BSC		0.85	BSC		0.50	BSC		0.50	BSC	
k	0.25	-	-	0.25	-	-	0.25	-	-	0.25	-	-
L	0.35	0.55	0.75	0.35	0.55	0.75	0.35	0.55	0.75	0.30	0.40	0.50
N	16			20			28			32		
ND	4			5			7			8		
NE	4			5			7			8		
P	0.00	0.42	0.60	0.00	0.42	0.60	0.00	0.42	0.60	0.00	0.42	0.60
g	0°			12°	0°		12°	0°		12°	0°	

NOTES:

1. DIE THICKNESS ALLOWABLE IS 0.305mm MAXIMUM (.012 INCHES MAXIMUM)
2. DIMENSIONING & TOLERANCES CONFORM TO ASME Y14.5M - 1994.
3. N IS THE NUMBER OF TERMINALS.
4. Nd IS THE NUMBER OF TERMINALS IN X-DIRECTION & Ne IS THE NUMBER OF TERMINALS IN Y-DIRECTION.
5. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.20 AND 0.25mm FROM TERMINAL TIP.
6. THE PIN #1 IDENTIFIER MUST BE EXISTED ON THE TOP SURFACE OF THE PACKAGE BY USING INDENTATION MARK OR INK/LASER MARKED. DETAILS OF PIN #1 IDENTIFIER IS OPTIONAL, BUT MUST BE LOCATED WITHIN ZONE INDICATED.
7. EXACT SHAPE AND SIZE OF THIS FEATURE IS OPTIONAL.
8. ALL DIMENSIONS ARE IN MILLIMETERS.
9. PACKAGE WARPAGE MAX 0.05mm.
10. APPLIED FOR EXPOSED PAD AND TERMINALS. EXCLUDE EMBEDDED PART OF EXPOSED PAD FROM MEASURING.
11. MEETS JEDEC MO220; EXCEPT DIMENSION "b".
12. APPLIED FOR EXPOSED PAD AND TERMINALS. EXCLUDE EMBEDDING PART OF EXPOSED PAD FROM MEASURING.
13. THIS PACKAGE OUTLINE APPLIES TO ANVIL SINGULATION (STEPPED SIDES).

EXPOSED PAD VARIATIONS						
PKG CODES	DE		E2			
	MIN.	NDM.	MAX.	MIN.	NDM.	MAX.
G1655-3	2.95	3.10	3.25	2.95	3.10	3.25
G2055-1	2.55	2.70	2.85	2.55	2.70	2.85
G2055-2	2.95	3.10	3.25	2.95	3.10	3.25
G2855-1	2.55	2.70	2.85	2.55	2.70	2.85
G2855-2	2.95	3.10	3.25	2.95	3.10	3.25
G3255-1	2.95	3.10	3.25	2.95	3.10	3.25

DALLAS SEMICONDUCTOR PROPRIETARY INFORMATION
TITLE: PACKAGE OUTLINE, 16,20,28,32L QFN,
5x5x0.90 MM
APPROVAL DOCUMENT CONTROL NO. REV. 1 1/2

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600

13

© 2007 Maxim Integrated Products

MAXIM is a registered trademark of Maxim Integrated Products, Inc.

MAX4610/MAX4611/MAX4612