

# **NCS20081, NCV20081, NCS20082, NCV20082, NCS20084, NCV20084**

## **Operational Amplifier, Rail-to-Rail Input and Output, 1.2 MHz**

The NCS2008 series operational amplifiers provide rail-to-rail input and output operation, 1.2 MHz bandwidth, and are available in single, dual, and quad configurations. Rail-to-rail operation gives designers use of the entire supply voltage range while taking advantage of the 1.2 MHz bandwidth. The NCS2008 can operate on supply voltages from 1.8 to 5.5 V over a temperature range from -40°C to 125°C. At a 1.8 V supply, this device has a slew rate of 0.4 V/ $\mu$ s while consuming only 42  $\mu$ A of quiescent current per channel. Since this is a CMOS device, high input impedance and low bias currents make it ideal for interfacing to a wide variety of signal sensors. The NCS2008 devices are available in a variety of compact packages.

### **Features**

- Rail-to-Rail Input and Output
- Wide Supply Range: 1.8 to 5.5 V
- Wide Bandwidth: 1.2 MHz
- High Slew Rate: 0.4 V/ $\mu$ s at  $V_S = 1.8$  V
- Low Supply Current: 42  $\mu$ A per Channel at  $V_S = 1.8$  V
- Low Input Bias Current: 1 pA Typical
- Wide Temperature Range: -40°C to 125°C
- Available in a Variety of Packages
- NCV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

### **Applications**

- Unity Gain Buffer
- Battery Powered / Low Quiescent Current Applications
- Low Cost Current Sensing
- Automotive



**ON Semiconductor®**

[www.onsemi.com](http://www.onsemi.com)



**SC70-5**  
CASE 419A



**TSOP-5/SOT23-5**  
CASE 483




**Micro8™/MSOP8**  
CASE 846A




**SOIC-8**  
CASE 751




**TSSOP-8**  
CASE 948S



**TSSOP-14**  
CASE 948G



**SOIC-14**  
CASE 751A



**UDFN6**  
CASE 517AP

### **DEVICE MARKING INFORMATION**

See general marking information in the device marking section on page 2 of this data sheet.

### **ORDERING INFORMATION**


See detailed ordering and shipping information on page 3 of this data sheet.

This document contains information on some products that are still under development. ON Semiconductor reserves the right to change or discontinue these products without notice.


# NCS20081, NCV20081, NCS20082, NCV20082, NCS20084, NCV20084

## MARKING DIAGRAMS


### Single Channel Configuration NCS20081, NCV20081



SC70-5  
CASE 419A




TSOP-5/SOT23-5  
CASE 483




UDFN6  
CASE 517AP


### Dual Channel Configuration NCS20082, NCV20082



Micro8™/MSOP8  
CASE 846A




SOIC-8  
CASE 751




TSSOP-8  
CASE 948S

### Quad Channel Configuration NCS20084, NCV20084



TSSOP-14  
CASE 948G



SOIC-14  
CASE 751A

XXXXX = Specific Device Code

A = Assembly Location

WL, L = Wafer Lot

Y = Year

WW, W = Work Week

G or ▀ = Pb-Free Package

(Note: Microdot may be in either location)

# NCS20081, NCV20081, NCS20082, NCV20082, NCS20084, NCV20084




Figure 1. Pin Connections

## ORDERING INFORMATION

| Device          | Configuration | Automotive | Marking  | Package        | Shipping <sup>†</sup>                           |
|-----------------|---------------|------------|----------|----------------|---|
| NCS20081SQ3T2G  | Single**      | No         | AAP      | SC70           | Contact local sales office for more information |
| NCS20081SN2T1G  |               |            | AER      | SOT23-5/TSOP-5 |   |
| NCS20081SN3T1G  |               |            | AEU      | SOT23-5/TSOP-5 |   |
| NCS20081MUTAG   |               |            | AP       | UDFN6          |   |
| NCV20081SQ3T2G* |               | Yes        | AAP      | SC70           |   |
| NCV20081SN2T1G* |               |            | AER      | SOT23-5/TSOP-5 |   |
| NCV20081SN3T1G* |               |            | AEU      | SOT23-5/TSOP-5 |   |
| NCV20081MUTAG*  |               |            | AP       | UDFN6          |   |
| NCS20082DMR2G   | Dual          | No         | 2K82     | Micro8/MSOP8   | Contact local sales office for more information |
| NCS20082DR2G    |               |            | NCS20082 | SOIC-8         |   |
| NCS20082DTBR2G  |               |            | K82      | TSSOP-8        |   |
| NCV20082DMR2G*  |               | Yes        | 2K82     | Micro8/MSOP8   |   |
| NCV20082DR2G*   |               |            | NCS20082 | SOIC-8         |   |
| NCV20082DTBR2G* |               |            | K82      | TSSOP-8        |   |
| NCS20084_       | Quad**        | No         | TBD      | SOIC-14        | Contact local sales office for more information |
| NCS20084_       |               |            | TBD      | SOP-14         |   |
| NCS20084_       |               |            | TBD      | TSSOP-14       |   |
| NCV20084_       |               | Yes        | TBD      | SOIC-14        |   |
| NCV20084_       |               |            | TBD      | SOP-14         |   |
| NCV20084_       |               |            | TBD      | TSSOP-14       |   |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D

\*NCV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable.

\*\*In Development. Not yet released.

# NCS20081, NCV20081, NCS20082, NCV20082, NCS20084, NCV20084

## ABSOLUTE MAXIMUM RATINGS (Note 1)

| Rating   | Symbol   | Limit   | Unit                |
|--|--|---|---------------------|
| Supply Voltage ( $V_{DD} - V_{SS}$ ) (Note 2)          | $V_S$  | 7   | V                   |
| Input Voltage  | $V_I$  | $V_{SS} - 0.5$ to $V_{DD} + 0.5$                              | V                   |
| Differential Input Voltage                             | $V_{ID}$   | $\pm V_S$   | V                   |
| Maximum Input Current                                  | $I_I$  | $\pm 10$  | mA                  |
| Maximum Output Current                                 | $I_O$  | $\pm 100$   | mA                  |
| Continuous Total Power Dissipation (Note 2)            | $P_D$  | 200   | mW                  |
| Maximum Junction Temperature                           | $T_J$  | 150   | °C                  |
| Storage Temperature Range                              | $T_{STG}$  | -65 to 150  | °C                  |
| Mounting Temperature (Infrared or Convection – 20 sec) | $T_{mount}$  | 260   | °C                  |
| ESD Capability (Note 3)                                | Human Body Model<br>Machine Model<br>Charge Device Model | ESD <sub>HBM</sub><br>ESD <sub>MM</sub><br>ESD <sub>CDM</sub> | 2000<br>100<br>2000 |
| Latch-Up Current (Note 4)                              | $I_{LU}$   | 100   | mA                  |
| Moisture Sensitivity Level (Note 5)                    | MSL  | Level 1   |                     |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Refer to ELECTRICAL CHARACTERISTICS for Safe Operating Area.
2. Continuous short circuit operation to ground at elevated ambient temperature can result in exceeding the maximum allowed junction temperature of 150°C. Output currents in excess of the maximum output current rating over the long term may adversely affect reliability. Shorting output to either VDD or VSS will adversely affect reliability.
3. This device series incorporates ESD protection and is tested by the following methods:  
ESD Human Body Model tested per AEC-Q100-002 (JEDEC standard: JESD22-A114)  
ESD Machine Model tested per AEC-Q100-003 (JEDEC standard: JESD22-A115)
4. Latch-up Current tested per JEDEC standard: JESD78
5. Moisture Sensitivity Level tested per IPC/JEDEC standard: J-STD-020A

## THERMAL INFORMATION

| Parameter                              | Symbol        | Channels | Package        | Single Layer Board (Note 6) | Multi-Layer Board (Note 7) | Unit |
|--|---------------|----------|----------------|-----------------------------|----------------------------|------|
| Junction to Ambient Thermal Resistance | $\theta_{JA}$ | Single   | SC-70          |                             |                            | °C/W |
|  |               |          | SOT23-5/TSOP-5 |                             |                            |      |
|  |               |          | UDFN6          |                             |                            |      |
|  |               | Dual     | Micro8/MSOP8   | 236                         | 167                        |      |
|  |               |          | SOIC-8         | 190                         | 131                        |      |
|  |               |          | TSSOP-8        | 253                         | 194                        |      |
|  |               | Quad     | SOIC-14        |                             |                            |      |
|  |               |          | SOP-14         |                             |                            |      |
|  |               |          | TSSOP-14       |                             |                            |      |

6. Value based on 1S standard PCB according to JEDEC51-3 with 1.0 oz copper and a 300 mm<sup>2</sup> copper area

7. Value based on 1S2P standard PCB according to JEDEC51-7 with 1.0 oz copper and a 100 mm<sup>2</sup> copper area

## OPERATING RANGES

| Parameter                  | Symbol    | Min            | Max            | Unit |
|----------------------------|-----------|----------------|----------------|------|
| Operating Supply Voltage   | $V_S$     | 1.8            | 5.5            | V    |
| Differential Input Voltage | $V_{ID}$  |                | $V_S$          | V    |
| Input Common Mode Range    | $V_{ICM}$ | $V_{SS} - 0.2$ | $V_{DD} + 0.2$ | V    |
| Ambient Temperature        | $T_A$     | -40            | 125            | °C   |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

# NCS20081, NCV20081, NCS20082, NCV20082, NCS20084, NCV20084

## ELECTRICAL CHARACTERISTICS AT $V_S = 1.8$ V

$T_A = 25^\circ\text{C}$ ;  $R_L \geq 10\text{ k}\Omega$ ;  $V_{CM} = V_{OUT}$  = mid-supply unless otherwise noted.

**Boldface** limits apply over the specified temperature range,  $T_A = -40^\circ\text{C}$  to  $125^\circ\text{C}$ . (Note 8)

| Parameter                            | Symbol                   | Conditions  | Min                    | Typ         | Max       | Unit                         |
|--------------------------------------|--------------------------|---|------------------------|-------------|-----------|------------------------------|
| <b>INPUT CHARACTERISTICS</b>         |                          |   |                        |             |           |                              |
| Input Offset Voltage                 | $V_{OS}$                 |   |                        | 0.5         | 3.5       | mV                           |
|                                      |                          |   |                        | <b>4</b>    |           | mV                           |
| Offset Voltage Drift                 | $\Delta V_{OS}/\Delta T$ |   |                        | 1           |           | $\mu\text{V}/^\circ\text{C}$ |
| Input Bias Current (Note 8)          | $I_{IB}$                 |   |                        | 1           |           | pA                           |
|                                      |                          |   |                        | <b>1500</b> |           | pA                           |
| Input Offset Current (Note 8)        | $I_{OS}$                 |   |                        | 1           |           | pA                           |
|                                      |                          |   |                        | <b>1100</b> |           | pA                           |
| Channel Separation                   | XTLK                     | DC  |                        | 125         |           | dB                           |
| Differential Input Resistance        | $R_{ID}$                 |   |                        | 10          |           | $\text{G}\Omega$             |
| Common Mode Input Resistance         | $R_{IN}$                 |   |                        | 10          |           | $\text{G}\Omega$             |
| Differential Input Capacitance       | $C_{ID}$                 |   |                        | 1           |           | pF                           |
| Common Mode Input Capacitance        | $C_{CM}$                 |   |                        | 5           |           | pF                           |
| Common Mode Rejection Ratio          | CMRR                     | $V_{CM} = V_{SS} - 0.2$ to $V_{DD} + 0.2$                 | 48                     | 73          |           | dB                           |
|                                      |                          | $V_{CM} = V_{SS} + 0.2$ to $V_{DD} - 0.2$                 | <b>45</b>              |             |           |                              |
| <b>OUTPUT CHARACTERISTICS</b>        |                          |   |                        |             |           |                              |
| Open Loop Voltage Gain               | $A_{VOL}$                |   | 86                     | 120         |           | dB                           |
|                                      |                          |   | <b>80</b>              |             |           |                              |
| Short Circuit Current                | $I_{SC}$                 | Output to positive rail, sinking current                  |                        | 15          |           | mA                           |
|                                      |                          | Output to negative rail, sourcing current                 |                        | 11          |           |                              |
| Output Voltage High                  | $V_{OH}$                 | Voltage output swing from positive rail                   |                        | 3           | 19        | mV                           |
|                                      |                          |   |                        | <b>20</b>   |           |                              |
| Output Voltage Low                   | $V_{OL}$                 | Voltage output swing from negative rail                   |                        | 3           | 19        | mV                           |
|                                      |                          |   |                        | <b>20</b>   |           |                              |
| <b>AC CHARACTERISTICS</b>            |                          |   |                        |             |           |                              |
| Unity Gain Bandwidth                 | UGBW                     |   |                        | 1.2         |           | MHz                          |
| Slew Rate at Unity Gain              | SR                       | $V_{ID} = 1.2\text{ Vpp}$ , Gain = 1                      |                        | 0.4         |           | $\text{V}/\mu\text{s}$       |
| Phase Margin                         | $\Psi_m$                 |   |                        | 60          |           | °                            |
| Gain Margin                          | $A_m$                    |   |                        | 19          |           | dB                           |
| Settling Time                        | $t_s$                    | $V_{IN} = 1.2\text{ Vpp}$ ,<br>Gain = 1                   | Settling time to 0.1%  | 5           |           | $\mu\text{s}$                |
|                                      |                          |   | Settling time to 0.01% | 6           |           |                              |
| Open Loop Output Impedance           | $Z_{OL}$                 | $f = 100\text{ Hz}$                                       |                        | 0.8         |           | $\Omega$                     |
| <b>NOISE CHARACTERISTICS</b>         |                          |   |                        |             |           |                              |
| Total Harmonic Distortion plus Noise | THD+N                    | $V_{IN} = 1.2\text{ Vpp}$ , $f = 1\text{ kHz}$ , $Av = 1$ |                        | 0.005       |           | %                            |
| Input Referred Voltage Noise         | $e_n$                    | $f = 1\text{ kHz}$  |                        | 30          |           | $\text{nV}/\sqrt{\text{Hz}}$ |
|                                      |                          | $f = 10\text{ kHz}$                                       |                        | 24          |           |                              |
| Input Referred Current Noise         | $i_n$                    | $f = 1\text{ kHz}$  |                        | 300         |           | $\text{fA}/\sqrt{\text{Hz}}$ |
| <b>SUPPLY CHARACTERISTICS</b>        |                          |   |                        |             |           |                              |
| Power Supply Rejection Ratio         | PSRR                     | No Load   | 67                     | 90          |           | dB                           |
|                                      |                          |   | <b>64</b>              |             |           |                              |
| Power Supply Quiescent Current       | $I_{DD}$                 | Per channel, no load                                      |                        | 42          | <b>60</b> | $\mu\text{A}$                |

8. Performance guaranteed over the indicated operating temperature range by design and/or characterization.

# NCS20081, NCV20081, NCS20082, NCV20082, NCS20084, NCV20084

## ELECTRICAL CHARACTERISTICS AT $V_S = 3.3$ V

$T_A = 25^\circ\text{C}$ ;  $R_L \geq 10 \text{ k}\Omega$ ;  $V_{CM} = V_{OUT}$  = mid-supply unless otherwise noted.

**Boldface** limits apply over the specified temperature range,  $T_A = -40^\circ\text{C}$  to  $125^\circ\text{C}$ . (Note 9)

| Parameter                            | Symbol                   | Conditions  | Min                    | Typ         | Max       | Unit                         |
|--------------------------------------|--------------------------|---|------------------------|-------------|-----------|------------------------------|
| <b>INPUT CHARACTERISTICS</b>         |                          |   |                        |             |           |                              |
| Input Offset Voltage                 | $V_{OS}$                 |   |                        | 0.5         | 3.5       | mV                           |
|                                      |                          |   |                        | <b>4</b>    |           | mV                           |
| Offset Voltage Drift                 | $\Delta V_{OS}/\Delta T$ |   |                        | 1           |           | $\mu\text{V}/^\circ\text{C}$ |
| Input Bias Current (Note 9)          | $I_{IB}$                 |   |                        | 1           |           | pA                           |
|                                      |                          |   |                        | <b>1500</b> |           | pA                           |
| Input Offset Current (Note 9)        | $I_{OS}$                 |   |                        | 1           |           | pA                           |
|                                      |                          |   |                        | <b>1100</b> |           | pA                           |
| Channel Separation                   | XTLK                     | DC  |                        | 125         |           | dB                           |
| Differential Input Resistance        | $R_{ID}$                 |   |                        | 10          |           | $\text{G}\Omega$             |
| Common Mode Input Resistance         | $R_{IN}$                 |   |                        | 10          |           | $\text{G}\Omega$             |
| Differential Input Capacitance       | $C_{ID}$                 |   |                        | 1           |           | pF                           |
| Common Mode Input Capacitance        | $C_{CM}$                 |   |                        | 5           |           | pF                           |
| Common Mode Rejection Ratio          | CMRR                     | $V_{CM} = V_{SS} - 0.2$ to $V_{DD} + 0.2$                   | 53                     | 76          |           | dB                           |
|                                      |                          | $V_{CM} = V_{SS} + 0.2$ to $V_{DD} - 0.2$                   | <b>48</b>              |             |           |                              |
| <b>OUTPUT CHARACTERISTICS</b>        |                          |   |                        |             |           |                              |
| Open Loop Voltage Gain               | $A_{VOL}$                |   | 90                     | 120         |           | dB                           |
|                                      |                          |   | <b>86</b>              |             |           |                              |
| Short Circuit Current                | $I_{SC}$                 | Output to positive rail, sinking current                    |                        | 15          |           | mA                           |
|                                      |                          | Output to negative rail, sourcing current                   |                        | 11          |           |                              |
| Output Voltage High                  | $V_{OH}$                 | Voltage output swing from positive rail                     |                        | 3           | 24        | mV                           |
|                                      |                          |   |                        | <b>25</b>   |           |                              |
| Output Voltage Low                   | $V_{OL}$                 | Voltage output swing from negative rail                     |                        | 3           | 24        | mV                           |
|                                      |                          |   |                        | <b>25</b>   |           |                              |
| <b>AC CHARACTERISTICS</b>            |                          |   |                        |             |           |                              |
| Unity Gain Bandwidth                 | UGBW                     |   |                        | 1.2         |           | MHz                          |
| Slew Rate at Unity Gain              | SR                       | $V_{IN} = 2.5 \text{ Vpp}$ , Gain = 1                       |                        | 0.4         |           | $\text{V}/\mu\text{s}$       |
| Phase Margin                         | $\Psi_m$                 |   |                        | 60          |           | °                            |
| Gain Margin                          | $A_m$                    |   |                        | 18          |           | dB                           |
| Settling Time                        | $t_s$                    | $V_{IN} = 2.5 \text{ Vpp}$ ,<br>Gain = 1                    | Settling time to 0.1%  | 5           |           | $\mu\text{s}$                |
|                                      |                          |   | Settling time to 0.01% | 6           |           |                              |
| Open Loop Output Impedance           | $Z_{OL}$                 | $f = 100 \text{ Hz}$  |                        | 0.8         |           | $\Omega$                     |
| <b>NOISE CHARACTERISTICS</b>         |                          |   |                        |             |           |                              |
| Total Harmonic Distortion plus Noise | THD+N                    | $V_{IN} = 2.5 \text{ Vpp}$ , $f = 1 \text{ kHz}$ , $Av = 1$ |                        | 0.005       |           | %                            |
| Input Referred Voltage Noise         | $e_n$                    | $f = 1 \text{ kHz}$   |                        | 30          |           | $\text{nV}/\sqrt{\text{Hz}}$ |
|                                      |                          | $f = 10 \text{ kHz}$  |                        | 24          |           |                              |
| Input Referred Current Noise         | $i_n$                    | $f = 1 \text{ kHz}$   |                        | 300         |           | $\text{fA}/\sqrt{\text{Hz}}$ |
| <b>SUPPLY CHARACTERISTICS</b>        |                          |   |                        |             |           |                              |
| Power Supply Rejection Ratio         | PSRR                     | No Load   | 67                     | 90          |           | dB                           |
|                                      |                          |   | <b>64</b>              |             |           |                              |
| Power Supply Quiescent Current       | $I_{DD}$                 | Per channel, no load  |                        | 42          | <b>60</b> | $\mu\text{A}$                |

9. Performance guaranteed over the indicated operating temperature range by design and/or characterization.

# NCS20081, NCV20081, NCS20082, NCV20082, NCS20084, NCV20084

## ELECTRICAL CHARACTERISTICS AT $V_S = 5.5$ V

$T_A = 25^\circ\text{C}$ ;  $R_L \geq 10 \text{ k}\Omega$ ;  $V_{CM} = V_{OUT}$  = mid-supply unless otherwise noted.

**Boldface** limits apply over the specified temperature range,  $T_A = -40^\circ\text{C}$  to  $125^\circ\text{C}$ . (Note 10)

| Parameter                            | Symbol                   | Conditions  | Min                    | Typ         | Max       | Unit                         |
|--------------------------------------|--------------------------|---|------------------------|-------------|-----------|------------------------------|
| <b>INPUT CHARACTERISTICS</b>         |                          |   |                        |             |           |                              |
| Input Offset Voltage                 | $V_{OS}$                 |   |                        | 0.5         | 3.5       | mV                           |
|                                      |                          |   |                        | <b>4</b>    |           | mV                           |
| Offset Voltage Drift                 | $\Delta V_{OS}/\Delta T$ |   |                        | 1           |           | $\mu\text{V}/^\circ\text{C}$ |
| Input Bias Current (Note 10)         | $I_{IB}$                 |   |                        | 1           |           | pA                           |
|                                      |                          |   |                        | <b>1500</b> |           | pA                           |
| Input Offset Current (Note 10)       | $I_{OS}$                 |   |                        | 1           |           | pA                           |
|                                      |                          |   |                        | <b>1100</b> |           | pA                           |
| Channel Separation                   | XTLK                     | DC  |                        | 125         |           | dB                           |
| Differential Input Resistance        | $R_{ID}$                 |   |                        | 10          |           | $\text{G}\Omega$             |
| Common Mode Input Resistance         | $R_{IN}$                 |   |                        | 10          |           | $\text{G}\Omega$             |
| Differential Input Capacitance       | $C_{ID}$                 |   |                        | 1           |           | pF                           |
| Common Mode Input Capacitance        | $C_{CM}$                 |   |                        | 5           |           | pF                           |
| Common Mode Rejection Ratio          | CMRR                     | $V_{CM} = V_{SS} - 0.2$ to $V_{DD} + 0.2$                 | 55                     | 79          |           | dB                           |
|                                      |                          | $V_{CM} = V_{SS} + 0.2$ to $V_{DD} - 0.2$                 | <b>51</b>              |             |           |                              |
| <b>OUTPUT CHARACTERISTICS</b>        |                          |   |                        |             |           |                              |
| Open Loop Voltage Gain               | $A_{VOL}$                |   | 90                     | 120         |           | dB                           |
|                                      |                          |   | <b>86</b>              |             |           |                              |
| Short Circuit Current                | $I_{SC}$                 | Output to positive rail, sinking current                  |                        | 15          |           | mA                           |
|                                      |                          | Output to negative rail, sourcing current                 |                        | 11          |           |                              |
| Output Voltage High                  | $V_{OH}$                 | Voltage output swing from positive rail                   |                        | 3           | 24        | mV                           |
|                                      |                          |   |                        | <b>25</b>   |           |                              |
| Output Voltage Low                   | $V_{OL}$                 | Voltage output swing from negative rail                   |                        | 3           | 24        | mV                           |
|                                      |                          |   |                        | <b>25</b>   |           |                              |
| <b>AC CHARACTERISTICS</b>            |                          |   |                        |             |           |                              |
| Unity Gain Bandwidth                 | UGBW                     |   |                        | 1.2         |           | MHz                          |
| Slew Rate at Unity Gain              | SR                       | $V_{ID} = 5 \text{ Vpp}$ , Gain = 1                       |                        | 0.4         |           | $\text{V}/\mu\text{s}$       |
| Phase Margin                         | $\Psi_m$                 |   |                        | 60          |           | °                            |
| Gain Margin                          | $A_m$                    |   |                        | 17          |           | dB                           |
| Settling Time                        | $t_s$                    | $V_{IN} = 5 \text{ Vpp}$ ,<br>Gain = 1                    | Settling time to 0.1%  | 5           |           | $\mu\text{s}$                |
|                                      |                          |   | Settling time to 0.01% | 6           |           |                              |
| Open Loop Output Impedance           | $Z_{OL}$                 | $f = 100 \text{ Hz}$                                      |                        | 0.8         |           | $\Omega$                     |
| <b>NOISE CHARACTERISTICS</b>         |                          |   |                        |             |           |                              |
| Total Harmonic Distortion plus Noise | THD+N                    | $V_{IN} = 5 \text{ Vpp}$ , $f = 1 \text{ kHz}$ , $Av = 1$ |                        | 0.005       |           | %                            |
| Input Referred Voltage Noise         | $e_n$                    | $f = 1 \text{ kHz}$                                       |                        | 30          |           | $\text{nV}/\sqrt{\text{Hz}}$ |
|                                      |                          | $f = 10 \text{ kHz}$                                      |                        | 24          |           |                              |
| Input Referred Current Noise         | $i_n$                    | $f = 1 \text{ kHz}$                                       |                        | 300         |           | $\text{fA}/\sqrt{\text{Hz}}$ |
| <b>SUPPLY CHARACTERISTICS</b>        |                          |   |                        |             |           |                              |
| Power Supply Rejection Ratio         | PSRR                     | No Load   | 67                     | 90          |           | dB                           |
|                                      |                          |   | <b>64</b>              |             |           |                              |
| Power Supply Quiescent Current       | $I_{DD}$                 | Per channel, no load                                      |                        | 48          | <b>70</b> | $\mu\text{A}$                |

10. Performance guaranteed over the indicated operating temperature range by design and/or characterization.

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

**TYPICAL PERFORMANCE CHARACTERISTICS**

$T_A = 25^\circ\text{C}$ ,  $R_L \geq 10 \text{ k}\Omega$ ,  $V_{CM} = V_{OUT} = \text{mid-supply}$  unless otherwise specified




Figure 2. Quiescent Current per Channel vs. Supply Voltage




Figure 3. Quiescent Current vs. Temperature




Figure 4. Offset Voltage vs. Supply Voltage




Figure 5. Offset Voltage vs. Temperature




Figure 6. Offset Voltage vs. Common Mode Voltage




Figure 7. Open-loop Gain and Phase Margin vs. Frequency

**TYPICAL PERFORMANCE CHARACTERISTICS**

$T_A = 25^\circ\text{C}$ ,  $R_L \geq 10 \text{ k}\Omega$ ,  $V_{CM} = V_{OUT}$  = mid-supply unless otherwise specified




Figure 8. Phase Margin vs. Capacitive Load




Figure 9. THD + N vs. Output Voltage




Figure 10. THD + N vs. Frequency




Figure 11. Input Voltage Noise vs. Frequency




Figure 12. Input Current Noise vs. Frequency




Figure 13. PSRR vs. Frequency

**TYPICAL PERFORMANCE CHARACTERISTICS**

$T_A = 25^\circ\text{C}$ ,  $R_L \geq 10 \text{ k}\Omega$ ,  $V_{CM} = V_{OUT}$  = mid-supply unless otherwise specified




Figure 14. CMRR vs. Frequency




Figure 15. Output Voltage High to Rail




Figure 16. Output Voltage Low to Rail




Figure 17. Non-Inverting Small Signal Transient Response




Figure 18. Inverting Small Signal Transient Response






Figure 19. Non-Inverting Large Signal Transient Response

**TYPICAL PERFORMANCE CHARACTERISTICS**


$T_A = 25^\circ\text{C}$ ,  $R_L \geq 10 \text{ k}\Omega$ ,  $V_{CM} = V_{OUT} = \text{mid-supply}$  unless otherwise specified




**Figure 20. Inverting Large Signal Transient Response**




**Figure 21. Input Bias and Offset Current vs. Temperature**




**Figure 22. Input Bias Current vs. Common Mode Voltage**



**Figure 23. 0.1 Hz to 10 Hz Noise**




**Figure 24. Channel Separation vs. Frequency**



**Figure 25. Output Impedance vs. Frequency**

**TYPICAL PERFORMANCE CHARACTERISTICS**



$T_A = 25^\circ\text{C}$ ,  $R_L \geq 10 \text{ k}\Omega$ ,  $V_{CM} = V_{OUT}$  = mid-supply unless otherwise specified



**Figure 26. Slew Rate vs. Temperature**

### PACKAGE DIMENSIONS

**SC-88A (SC-70-5/SOT-353)**  
CASE 419A-02  
ISSUE L




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 419A-01 OBSOLETE. NEW STANDARD 419A-02.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.





| DIM | INCHES    |       | MILLIMETERS |      |
|-----|-----------|-------|-------------|------|
|     | MIN       | MAX   | MIN         | MAX  |
| A   | 0.071     | 0.087 | 1.80        | 2.20 |
| B   | 0.045     | 0.053 | 1.15        | 1.35 |
| C   | 0.031     | 0.043 | 0.80        | 1.10 |
| D   | 0.004     | 0.012 | 0.10        | 0.30 |
| G   | 0.026 BSC |       | 0.65 BSC    |      |
| H   | ---       | 0.004 | ---         | 0.10 |
| J   | 0.004     | 0.010 | 0.10        | 0.25 |
| K   | 0.004     | 0.012 | 0.10        | 0.30 |
| N   | 0.008 REF |       | 0.20 REF    |      |
| S   | 0.079     | 0.087 | 2.00        | 2.20 |

### SOLDER FOOTPRINT



PACKAGE DIMENSIONS


**TSOP-5**  
CASE 483  
ISSUE L



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
  2. CONTROLLING DIMENSION: MILLIMETERS.
  3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
  4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.15 PER SIDE. DIMENSION A.
  5. OPTIONAL CONSTRUCTION: AN ADDITIONAL TRIMMED LEAD IS ALLOWED IN THIS LOCATION. TRIMMED LEAD NOT TO EXTEND MORE THAN 0.2 FROM BODY.


|     | MILLIMETERS |      |
|-----|-------------|------|
| DIM | MIN         | MAX  |
| A   | 3.00 BSC    |      |
| B   | 1.50 BSC    |      |
| C   | 0.90        | 1.10 |
| D   | 0.25        | 0.50 |
| G   | 0.95 BSC    |      |
| H   | 0.01        | 0.10 |
| J   | 0.10        | 0.26 |
| K   | 0.20        | 0.60 |
| M   | 0 °         | 10 ° |
| S   | 2.50        | 3.00 |

**SOLDERING FOOTPRINT\***



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

PACKAGE DIMENSIONS




\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

PACKAGE DIMENSIONS


**Micro8™**  
CASE 846A-02  
ISSUE J

- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: MILLIMETER.
  3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED 0.15 (.006) PER SIDE.
  4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
  5. 846A-01 OBSOLETE, NEW STANDARD 846A-02.




| DIM            | MILLIMETERS |      |      | INCHES    |       |       |
|----------------|-------------|------|------|-----------|-------|-------|
|                | MIN         | NOM  | MAX  | MIN       | NOM   | MAX   |
| A              | —           | —    | 1.10 | —         | —     | 0.043 |
| A1             | 0.05        | 0.08 | 0.15 | 0.002     | 0.003 | 0.006 |
| b              | 0.25        | 0.33 | 0.40 | 0.010     | 0.013 | 0.016 |
| c              | 0.13        | 0.18 | 0.23 | 0.005     | 0.007 | 0.009 |
| D              | 2.90        | 3.00 | 3.10 | 0.114     | 0.118 | 0.122 |
| E              | 2.90        | 3.00 | 3.10 | 0.114     | 0.118 | 0.122 |
| e              | 0.65 BSC    |      |      | 0.026 BSC |       |       |
| L              | 0.40        | 0.55 | 0.70 | 0.016     | 0.021 | 0.028 |
| H <sub>E</sub> | 4.75        | 4.90 | 5.05 | 0.187     | 0.193 | 0.199 |

**RECOMMENDED  
SOLDERING FOOTPRINT\***



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

PACKAGE DIMENSIONS




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. 751-01 THRU 751-06 ARE OBSOLETE. NEW STANDARD IS 751-07.

| DIM | MILLIMETERS |           | INCHES |       |
|-----|-------------|-----------|--------|-------|
|     | MIN         | MAX       | MIN    | MAX   |
| A   | 4.80        | 5.00      | 0.189  | 0.197 |
| B   | 3.80        | 4.00      | 0.150  | 0.157 |
| C   | 1.35        | 1.75      | 0.053  | 0.069 |
| D   | 0.33        | 0.51      | 0.013  | 0.020 |
| G   | 1.27 BSC    | 0.050 BSC |        |       |
| H   | 0.10        | 0.25      | 0.004  | 0.010 |
| J   | 0.19        | 0.25      | 0.007  | 0.010 |
| K   | 0.40        | 1.27      | 0.016  | 0.050 |
| M   | 0 °         | 8 °       | 0 °    | 8 °   |
| N   | 0.25        | 0.50      | 0.010  | 0.020 |
| S   | 5.80        | 6.20      | 0.228  | 0.244 |

- STYLE 11:  
 PIN 1. SOURCE 1  
 2. GATE 1  
 3. SOURCE 2  
 4. GATE 2  
 5. DRAIN 2  
 6. DRAIN 2  
 7. DRAIN 1  
 8. DRAIN 1


SOLDERING FOOTPRINT\*



SCALE 6:1 ( $\frac{\text{mm}}{\text{inches}}$ )

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

PACKAGE DIMENSIONS







NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH. PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
6. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-.

| DIM | MILLIMETERS |           | INCHES |       |
|-----|-------------|-----------|--------|-------|
|     | MIN         | MAX       | MIN    | MAX   |
| A   | 2.90        | 3.10      | 0.114  | 0.122 |
| B   | 4.30        | 4.50      | 0.169  | 0.177 |
| C   | ---         | 1.10      | ---    | 0.043 |
| D   | 0.05        | 0.15      | 0.002  | 0.006 |
| F   | 0.50        | 0.70      | 0.020  | 0.028 |
| G   | 0.65 BSC    | 0.026 BSC |        |       |
| J   | 0.09        | 0.20      | 0.004  | 0.008 |
| J1  | 0.09        | 0.16      | 0.004  | 0.006 |
| K   | 0.19        | 0.30      | 0.007  | 0.012 |
| K1  | 0.19        | 0.25      | 0.007  | 0.010 |
| L   | 6.40 BSC    | 0.252 BSC |        |       |
| M   | 0°          | 8°        | 0°     | 8°    |

PACKAGE DIMENSIONS


SOIC-14 NB  
CASE 751A-03  
ISSUE K



NOTES:  
 1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.  
 2. CONTROLLING DIMENSION: MILLIMETERS.  
 3. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE PROTRUSION SHALL BE 0.13 TOTAL IN EXCESS OF AT MAXIMUM MATERIAL CONDITION.  
 4. DIMENSIONS D AND E DO NOT INCLUDE MOLD PROTRUSIONS.  
 5. MAXIMUM MOLD PROTRUSION 0.15 PER SIDE.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 1.35        | 1.75 | 0.054     | 0.068 |
| A1  | 0.10        | 0.25 | 0.004     | 0.010 |
| A3  | 0.19        | 0.25 | 0.008     | 0.010 |
| b   | 0.35        | 0.49 | 0.014     | 0.019 |
| D   | 8.55        | 8.75 | 0.337     | 0.344 |
| E   | 3.80        | 4.00 | 0.150     | 0.157 |
| e   | 1.27 BSC    |      | 0.050 BSC |       |
| H   | 5.80        | 6.20 | 0.228     | 0.244 |
| h   | 0.25        | 0.50 | 0.010     | 0.019 |
| L   | 0.40        | 1.25 | 0.016     | 0.049 |
| M   | 0 °         | 7 °  | 0 °       | 7 °   |


SOLDERING FOOTPRINT\*



DIMENSIONS: MILLIMETERS

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

## PACKAGE DIMENSIONS




## NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE  $-W-$ .

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 4.90        | 5.10 | 0.193     | 0.200 |
| B   | 4.30        | 4.50 | 0.169     | 0.177 |
| C   | —           | 1.20 | —         | 0.047 |
| D   | 0.05        | 0.15 | 0.002     | 0.006 |
| F   | 0.50        | 0.75 | 0.020     | 0.030 |
| G   | 0.65 BSC    | —    | 0.026 BSC | —     |
| H   | 0.50        | 0.60 | 0.020     | 0.024 |
| J   | 0.09        | 0.20 | 0.004     | 0.008 |
| J1  | 0.09        | 0.16 | 0.004     | 0.006 |
| K   | 0.19        | 0.30 | 0.007     | 0.012 |
| K1  | 0.19        | 0.25 | 0.007     | 0.010 |
| L   | 6.40 BSC    | —    | 0.252 BSC | —     |
| M   | 0°          | 8°   | 0°        | 8°    |

## SOLDERING FOOTPRINT



DIMENSIONS: MILLIMETERS

Micro8 is a trademark of International Rectifier

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

## LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada

Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5817-1050

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative