

Schottky Barrier Rectifier

SBL6040PT

FEATURES



- With TO-247 packaging
- Low leakage current, low power loss, high efficiency
- High frequency operation
- High surge capability
- Low stored charge majority carrier conduction
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Switching power supply
- High frequency inverters
- Freewheeling diodes
- Reverse battery protection
- Polarity protection applications

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{RRM} V_{RMS} V_R	Peak Repetitive Reverse Voltage RMS Voltage DC Blocking Voltage	40	V
$I_{F(AV)}$	Average Rectified Forward Current@ $T_c=150^\circ\text{C}$	60	A
I_{FSM}	Nonrepetitive Peak Surge Current (8.3ms single half sine-wave superimposed on rated load conditions) $t_p=10\text{ms}$	500	A
T_J	Junction Temperature	-65~150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-65~150	$^\circ\text{C}$



Schottky Barrier Rectifier**SBL6040PT****THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	0.5	$^{\circ}C/W$

ELECTRICAL CHARACTERISTICS (Pulse Test: Pulse Width=300 μ s, Duty Cycle $\leq$ 1%)

SYMBOL	PARAMETER	CONDITIONS	MAX	UNIT
V_F	Maximum Instantaneous Forward Voltage	$I_F=30; T_j=25^{\circ}C$	0.55	V
I_R	Maximum Instantaneous Reverse Current	$V_R = \text{rated } V_{RRM}; T_j=25^{\circ}C$	20	mA
		$V_R = \text{rated } V_{RRM}; T_j=100^{\circ}C$	200	