

N-channel 800 V, 2.75 Ω typ., 2 A MDmesh™ K5 Power MOSFET in a DPAK package

Datasheet - production data





Figure 1: Internal schematic diagram



AM01476v1

Table 1: Device summary

| Order code | Marking | Package | Packing |
|------------|---------|---------|---------------|
| STD3LN80K5 | 3LN80K5 | DPAK | Tape and reel |

Features

| Order code | V _{DS} | R _{DS(on)} max | I _D |
|------------|-----------------|-------------------------|----------------|
| STD3LN80K5 | 800 V | 3.25 Ω | 2 A |

- Industry's lowest R_{DS(on)} x area
- Industry's best FoM (figure of merit)
- Ultra-low gate charge
- 100% avalanche tested
- Zener-protected

Applications

- Switching applications

Description

This very high voltage N-channel Power MOSFET is designed using MDmesh™ K5 technology based on an innovative proprietary vertical structure. The result is a dramatic reduction in on-resistance and ultra-low gate charge for applications requiring superior power density and high efficiency.

Contents

| | | |
|----------|--|-----------|
| 1 | Electrical ratings | 3 |
| 2 | Electrical characteristics | 4 |
| | 2.1 Electrical characteristics (curves)..... | 6 |
| 3 | Test circuits | 8 |
| 4 | Package information | 9 |
| | 4.1 DPAK package information | 9 |
| | 4.2 DPAK packing information | 12 |
| 5 | Revision history | 14 |

1 Electrical ratings

Table 2: Absolute maximum ratings

| Symbol | Parameter | Value | Unit |
|---------------|---|-------------|------------------|
| V_{GS} | Gate-source voltage | ± 30 | V |
| I_D | Drain current (continuous) at $T_C = 25\text{ }^\circ\text{C}$ | 2 | A |
| I_D | Drain current (continuous) at $T_C = 100\text{ }^\circ\text{C}$ | 1.25 | A |
| $I_D^{(1)}$ | Drain current (pulsed) | 8 | A |
| P_{TOT} | Total dissipation at $T_C = 25\text{ }^\circ\text{C}$ | 45 | W |
| $dv/dt^{(2)}$ | Peak diode recovery voltage slope | 4.5 | V/ns |
| $dv/dt^{(3)}$ | MOSFET dv/dt ruggedness | 50 | |
| T_{stg} | Storage temperature range | - 55 to 150 | $^\circ\text{C}$ |
| T_j | Operating junction temperature range | | |

Notes:

(1)Pulse width limited by safe operating area.

(2) $I_{SD} \leq 2\text{ A}$, $di/dt \leq 100\text{ A}/\mu\text{s}$; $V_{DSpeak} < V_{(BR)DSS}$, $V_{DD} = 640\text{ V}$

(3) $V_{DS} \leq 640\text{ V}$.

Table 3: Thermal data

| Symbol | Parameter | Value | Unit |
|---------------------|----------------------------------|-------|---------------------------|
| $R_{thj-case}$ | Thermal resistance junction-case | 2.78 | $^\circ\text{C}/\text{W}$ |
| $R_{thj-pcb}^{(1)}$ | Thermal resistance junction-pcb | 50 | $^\circ\text{C}/\text{W}$ |

Notes:

(1)When mounted on 1inch² FR-4 board, 2 oz Cu.

Table 4: Avalanche characteristics

| Symbol | Parameter | Value | Unit |
|----------|--|-------|------|
| I_{AR} | Avalanche current, repetitive or not repetitive (pulse width limited by T_{jmax}) | 0.7 | A |
| E_{AS} | Single pulse avalanche energy (starting $T_j = 25\text{ }^\circ\text{C}$, $I_D = I_{AR}$; $V_{DD} = 50\text{ V}$) | 155 | mJ |

2 Electrical characteristics

(T_C = 25 °C unless otherwise specified)

Table 5: On /off states

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|----------------------|-----------------------------------|--|------|------|------|------|
| V _{(BR)DSS} | Drain-source breakdown voltage | I _D = 1 mA, V _{GS} = 0 V | 800 | | | V |
| I _{DSS} | Zero gate voltage drain current | V _{DS} = 800 V, V _{GS} = 0 V | | | 1 | μA |
| | | V _{DS} = 800 V, V _{GS} = 0 V, T _C = 125 °C ⁽¹⁾ | | | 50 | μA |
| I _{GSS} | Gate body leakage current | V _{GS} = ± 20 V, V _{GS} = 0 V | | | ±10 | μA |
| V _{GS(th)} | Gate threshold voltage | V _{DS} = V _{GS} , I _D = 100 μA | 3 | 4 | 5 | V |
| R _{DS(on)} | Static drain-source on-resistance | V _{GS} = 10 V, I _D = 1 A | | 2.75 | 3.25 | Ω |

Notes:

⁽¹⁾Defined by design, not subject to production test.

Table 6: Dynamic

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|---------------------------------|---------------------------------------|--|------|------|------|------|
| C _{iss} | Input capacitance | V _{DS} = 100 V, f = 1 MHz, V _{GS} = 0 V | - | 102 | - | pF |
| C _{oss} | Output capacitance | | - | 11 | - | pF |
| C _{rss} | Reverse transfer capacitance | | - | 0.1 | - | pF |
| C _{otr} ⁽¹⁾ | Equivalent capacitance time related | V _{DS} = 0 to 640 V, V _{GS} = 0 V | - | 20 | - | pF |
| C _{oer} ⁽²⁾ | Equivalent capacitance energy related | | - | 7 | - | pF |
| R _G | Intrinsic gate resistance | f = 1 MHz, I _D = 0 A | - | 12 | - | Ω |
| Q _g | Total gate charge | V _{DD} = 640 V, I _D = 2 A, V _{GS} = 10 V (see Figure 15: "Test circuit for gate charge behavior") | - | 2.63 | - | nC |
| Q _{gs} | Gate-source charge | | - | 0.91 | - | nC |
| Q _{gd} | Gate-drain charge | | - | 1.53 | - | nC |

Notes:

⁽¹⁾Time related is defined as a constant equivalent capacitance giving the same charging time as C_{oss} when V_{DS} increases from 0 to 80% V_{DSS}

⁽²⁾Energy related is defined as a constant equivalent capacitance giving the same stored energy as C_{oss} when V_{DS} increases from 0 to 80% V_{DSS}

Table 7: Switching times

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|--------------|---------------------|--|------|------|------|------|
| $t_{d(on)}$ | Turn-on delay time | $V_{DD} = 400\text{ V}$, $I_D = 1\text{ A}$, $R_G = 4.7\ \Omega$, $V_{GS} = 10\text{ V}$ (see Figure 14: "Test circuit for resistive load switching times" and Figure 19: "Switching time waveform") | - | 6.2 | - | ns |
| t_r | Rise time | | - | 7 | - | ns |
| $t_{d(off)}$ | Turn-off delay time | | - | 30 | - | ns |
| t_f | Fall time | | - | 26 | - | ns |

Table 8: Source drain diode

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|-----------------|-------------------------------|---|------|------|------|---------------|
| I_{SD} | Source-drain current | | - | | 2 | A |
| $I_{SDM}^{(1)}$ | Source-drain current (pulsed) | | - | | 8 | A |
| $V_{SD}^{(2)}$ | Forward on voltage | $I_{SD} = 2\text{ A}$, $V_{GS} = 0\text{ V}$ | - | | 1.5 | V |
| t_{rr} | Reverse recovery time | $I_{SD} = 2\text{ A}$, $di/dt = 100\text{ A}/\mu\text{s}$, $V_{DD} = 60\text{ V}$ (see Figure 16: "Test circuit for inductive load switching and diode recovery times") | - | 210 | | ns |
| Q_{rr} | Reverse recovery charge | | - | 0.8 | | μC |
| I_{RRM} | Reverse recovery current | | - | 7.6 | | A |
| t_{rr} | Reverse recovery time | $I_{SD} = 2\text{ A}$, $di/dt = 100\text{ A}/\mu\text{s}$, $V_{DD} = 60\text{ V}$, $T_J = 150\text{ }^\circ\text{C}$, (see Figure 16: "Test circuit for inductive load switching and diode recovery times") | - | 345 | | ns |
| Q_{rr} | Reverse recovery charge | | - | 1.2 | | μC |
| I_{RRM} | Reverse recovery current | | - | 7.2 | | A |

Notes:

(1)Pulse width limited by safe operating area.




(2)Pulsed: pulse duration = 300 μs , duty cycle 1.5%.







Table 9: Gate-source Zener diode

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|---------------|-------------------------------|---|------|------|------|------|
| $V_{(BR)GSO}$ | Gate-source breakdown voltage | $I_{GS} = \pm 1\text{ mA}$, $I_D = 0\text{ A}$ | 30 | - | - | V |

The built-in back-to-back Zener diodes are specifically designed to enhance the ESD performance of the device. The Zener voltage facilitates efficient and cost-effective device integrity protection, thus eliminating the need for additional external componentry.


2.1 Electrical characteristics (curves)






3 Test circuits

Figure 14: Test circuit for resistive load switching times




AM01468v1

Figure 15: Test circuit for gate charge behavior




AM01469v10

Figure 16: Test circuit for inductive load switching and diode recovery times




AM01470v1

Figure 17: Unclamped inductive load test circuit




AM01471v1

Figure 18: Unclamped inductive waveform



AM01472v1

Figure 19: Switching time waveform



AM01473v1

4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

4.1 DPAK package information

Figure 20: DPAK (TO-252) type A package outline





Table 10: DPAK (TO-252) type A mechanical data

| Dim. | mm | | |
|------|------|------|-------|
| | Min. | Typ. | Max. |
| A | 2.20 | | 2.40 |
| A1 | 0.90 | | 1.10 |
| A2 | 0.03 | | 0.23 |
| b | 0.64 | | 0.90 |
| b4 | 5.20 | | 5.40 |
| c | 0.45 | | 0.60 |
| c2 | 0.48 | | 0.60 |
| D | 6.00 | | 6.20 |
| D1 | 4.95 | 5.10 | 5.25 |
| E | 6.40 | | 6.60 |
| E1 | 4.60 | 4.70 | 4.80 |
| e | 2.16 | 2.28 | 2.40 |
| e1 | 4.40 | | 4.60 |
| H | 9.35 | | 10.10 |
| L | 1.00 | | 1.50 |
| (L1) | 2.60 | 2.80 | 3.00 |
| L2 | 0.65 | 0.80 | 0.95 |
| L4 | 0.60 | | 1.00 |
| R | | 0.20 | |
| V2 | 0° | | 8° |

Figure 21: DPAK (TO-252) recommended footprint (dimensions are in mm)



4.2 DPAK packing information

Figure 22: DPAK (TO-252) tape outline




Figure 23: DPAK (TO-252) reel outline




Table 11: DPAK (TO-252) tape and reel mechanical data

| Tape | | | Reel | | |
|------|------|------|-----------|------|------|
| Dim. | mm | | Dim. | mm | |
| | Min. | Max. | | Min. | Max. |
| A0 | 6.8 | 7 | A | | 330 |
| B0 | 10.4 | 10.6 | B | 1.5 | |
| B1 | | 12.1 | C | 12.8 | 13.2 |
| D | 1.5 | 1.6 | D | 20.2 | |
| D1 | 1.5 | | G | 16.4 | 18.4 |
| E | 1.65 | 1.85 | N | 50 | |
| F | 7.4 | 7.6 | T | | 22.4 |
| K0 | 2.55 | 2.75 | | | |
| P0 | 3.9 | 4.1 | Base qty. | | 2500 |
| P1 | 7.9 | 8.1 | Bulk qty. | | 2500 |
| P2 | 1.9 | 2.1 | | | |
| R | 40 | | | | |
| T | 0.25 | 0.35 | | | |
| W | 15.7 | 16.3 | | | |

5 Revision history

Table 12: Document revision history

| Date | Revision | Changes |
|-------------|----------|---|
| 13-May-2015 | 1 | Initial release |
| 27-Jul-2016 | 2 | Updated title and features in cover page. Updated <i>Section 1: "Electrical ratings"</i> and <i>Section 2: "Electrical characteristics"</i> . Added <i>Section 2.1: "Electrical characteristics (curves)"</i> . Document status promoted from preliminary to production data. Minor text changes. |

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2016 STMicroelectronics – All rights reserved