


**STPS2H100A/U**

## HIGH VOLTAGE POWER SCHOTTKY RECTIFIER

### MAIN PRODUCT CHARACTERISTICS

I <sub>F(AV)</sub>	2 A
V <sub>RRM</sub>	100 V
T <sub>j</sub> (max)	175 °C
V <sub>F</sub> (max)	0.65 V



### FEATURES AND BENEFITS

- NEGLIGIBLE SWITCHING LOSSES
- HIGH JUNCTION TEMPERATURE CAPABILITY
- LOW LEAKAGE CURRENT
- GOOD TRADE OFF BETWEEN LEAKAGE CURRENT AND FORWARD VOLTAGE DROP
- AVALANCHE RATED

### DESCRIPTION

Schottky rectifier designed for high frequency miniature Switched Mode Power Supplies such as adaptors and on board DC/DC converters.

Packaged in SMA or SMB.

### ABSOLUTE RATINGS (limiting values)

Symbol	Parameter		Value	Unit
V <sub>RRM</sub>	Repetitive peak reverse voltage		100	V
I <sub>F(RMS)</sub>	RMS forward current		10	A
I <sub>F(AV)</sub>	Average forward current	T <sub>L</sub> = 130°C δ = 0.5	2	A
I <sub>FSM</sub>	Surge non repetitive forward current	tp = 10 ms sinusoidal	75	A
I <sub>RRM</sub>	Repetitive peak reverse current	tp=2 μs F=1kHz square	1	A
I <sub>RSRM</sub>	Non repetitive peak reverse current	tp = 100 μs square	1	A
T <sub>stg</sub>	Storage temperature range		- 65 to + 175	°C
T <sub>j</sub>	Maximum operating junction temperature		175	°C
dV/dt	Critical rate of rise of reverse voltage		10000	V/μs

## STPS2H100A/U

### THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
R <sub>th(j-l)</sub>	Junction to lead	SMA	30
		SMB	25

### STATIC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Tests conditions		Min.	Typ.	Max.	Unit
I <sub>R</sub> *	Reverse leakage current	T <sub>j</sub> = 25°C	V <sub>R</sub> = V <sub>RRM</sub>			1	μA
		T <sub>j</sub> = 125°C			0.4	1	mA
V <sub>F</sub> **	Forward voltage drop	T <sub>j</sub> = 25°C	I <sub>F</sub> = 2 A			0.79	V
		T <sub>j</sub> = 125°C	I <sub>F</sub> = 2 A		0.6	0.65	
		T <sub>j</sub> = 25°C	I <sub>F</sub> = 4 A			0.88	
		T <sub>j</sub> = 125°C	I <sub>F</sub> = 4 A		0.69	0.74	


Pulse test : \* tp = 5 ms, δ < 2%

\*\* tp = 380 μs, δ < 2%


To evaluate the maximum conduction losses use the following equation :

$$P = 0.56 I_{F(AV)} + 0.045 I_{F}^2(RMS)$$


**Fig. 1:** Average forward power dissipation versus average forward current.




**Fig. 2:** Average forward current versus ambient temperature (δ=0.5).




**Fig. 3:** Non repetitive surge peak forward current versus overload duration (maximum values) (SMB).




**Fig. 5:** Relative variation of thermal impedance junction to ambient versus pulse duration (SMB).




**Fig. 7:** Reverse leakage current versus reverse voltage applied (typical values).




**Fig. 4:** Non repetitive surge peak forward current versus overload duration (maximum values) (SMA).



**Fig. 6:** Relative variation of thermal impedance junction to ambient versus pulse duration (SMA).




**Fig. 8:** Junction capacitance versus reverse voltage applied (typical values).




## STPS2H100A/U


**Fig. 9:** Thermal resistance junction to ambient versus copper surface under each lead  
(Epoxy printed circuit board FR4, copper thickness: 35 $\mu$ m) (SMB).



**Fig. 10:** Thermal resistance junction to ambient versus copper surface under each lead  
(Epoxy printed circuit board FR4, copper thickness: 35 $\mu$ m) (SMA).




**Fig. 11:** Forward voltage drop versus forward current .



**PACKAGE MECHANICAL DATA**  
**SMA**

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.70	0.075	0.106
A2	0.05	0.20	0.002	0.008
b	1.25	1.65	0.049	0.065
c	0.15	0.41	0.006	0.016
E	4.80	5.60	0.189	0.220
E1	3.95	4.60	0.156	0.181
D	2.25	2.95	0.089	0.116
L	0.75	1.60	0.030	0.063


**FOOT PRINT (in millimeters)**

## STPS2H100A/U

### PACKAGE MECHANICAL DATA SMB

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.075	0.096
A2	0.05	0.20	0.002	0.008
b	1.95	2.20	0.077	0.087
c	0.15	0.41	0.006	0.016
E	5.10	5.60	0.201	0.220
E1	4.05	4.60	0.159	0.181
D	3.30	3.95	0.130	0.156
L	0.75	1.60	0.030	0.063

FOOT PRINT (in millimeters)



Ordering type	Marking	Package	Weight	Base qty	Delivery mode
STPS2H100A	S21	SMA	0.068g	5000	Tape & reel
STPS2H100U	G21	SMB	0.107g	2500	Tape & reel

- Band indicates cathode
- Epoxy meets UL94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied.

STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 1999 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia

Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

<http://www.st.com>