



DUAL POWER AMPLIFIER TDA2822


GENERAL DESCRIPTION

The TDA2822 is a monolithic integrated circuit in 8 lead Minidip package. It is intended for use as dual audio power amplifier in portable cassette tape players and radios.

FEATURES


- Dual Low-voltage power amplifier
- Supply voltage down to 1.8V
- Low crossover distortion
- Low quiescent current
- Bridge or stereo configuration

BLOCK DIAGRAM




PINNING


Outline Drawing



DIP8



SOP8



MAXIMUM RATINGS

Characteristics	Symbol	Value	Unit
Supply Voltage	Vcc	15	V
Output Peak Current	Ipk	1	A
Total Power Dissipation(at Tamb=50°C)	P _D	1	W
Total Power Dissipation(at Tcase=50°C)	P _D	1.4	W
Operating Ambient Temperature Range	T _a	-20~70	°C
Storage Temperature Range	T _{stg}	-40~150	°C

ELECTRICAL CHARACTERISTICS

1. Stereo Test Circuit(Unless otherwise specified Vcc=6V,Tamb=25°C)


Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Supply Voltage	Vcc		1.8		15	V
Quiescent Output Voltage	Vo			2.7		V
		Vcc=3V		1.2		V
Quiescent Drain Current	Id			6	9	mA
Input Bias Current	I _{BA}			100		nA
Output Power (Each Channel)	Po	d=10% f=1kHz Vcc=3V R _L =4 Vcc=3V R _L =32		110		mW
		d=10% f=1kHz Vcc=9V R _L =8 Vcc=6V R _L =4 Vcc=4.5V R _L =4	0.4	1 0.65 0.32		W
Distortion	THD	Po=0.5W R _L =8 f=1kHz Vcc=9V		0.3		%
Closed Loop Voltage Gain	Avf	f=1kHz		40		dB
Channel Balance	ΔAvf				± 1	dB
Input Resistance	R _i	f=1kHz	100			k
Total Input Noise	V _{NI}	R _s =10k B=Cure A		2		μV
		R _s =10k B=22Hz to 22kHz		3		
Supply Voltage rejection	SVR	f=100Hz C ₁ =C ₂ =100 μF	24	30		dB
Channel Separation	CSR	f=1kHz		50		dB

2.Bridge Test Circuit (Unless otherwise specified V_{cc}=6V,T_{amb}=25°C)


Characteristic	Sym -bol	Test Condition	Min.	Typ.	Max.	Unit
Supply Voltage	V _{cc}		1.8		15	V
Quiescent Drain Current	I _d	R _L =∞		6	9	mA
Output Offset Voltage (Between the Outputs)	V _{os}	R _L =8			± 50	mV
Input Bias Current	I _b		100			nA
Output Power	P _o	d=10% f=1kHz V _{cc} =9V R _L =16 V _{cc} =6V R _L =8 V _{cc} =4.5V R _L =8 V _{cc} =4.5V R _L =4		2		
		V _{cc} =3V R _L =4 V _{cc} =2V R _L =4	200	350 80		mW
Distortion	THD	P _o =0.5W R _L =8 f=1kHz		0.2		%
Closed Loop Voltage Gain	A _{vf}	f=1kHz		40		dB
Input Resistance	R _i	f=1kHz	100			k
Total Input Noise	V _{NI}	R _s =10k Curve A		2.5		μ V
		R _s =10k B=22Hz to 22kHz		3		
Supply Voltage Rejection	S _{VR}	f=100Hz		40		dB
Power Bandwidth (-3dB)	B	R _L =8 P _o =1W		120		kHz

TEST CIRCUIT

1. STEREO TEST CIRCUIT




2. BRIDGE TEST CIRCUIT




APPLICATION CIRCUIT


1. Typical application in portable players




2. Application circuit for portable radio receivers




3. Portable radio cassette players



4. Portable stereo radios



5. Low cost application for portables (using only one 100μF output capacitor)



CHARACTERISTICS CURVES

Fig. 4 - Quiescent current vs.
supply voltage




Fig. 5 - Supply voltage re-
jection vs. frequency (stereo)

