

**Data Sheet****HMC8412****FEATURES**

- Low noise figure: 1.4 dB typical**
- Single positive supply (self biased)**
- High gain: ≤15.5 dB typical**
- High OIP3: ≤33 dBm typical**
- RoHS-compliant, 2 mm × 2 mm, 6-lead LFCSP**


**APPLICATIONS**

- Test instrumentation**
- Telecommunications**
- Military radar and communication**
- Electronic warfare**
- Aerospace**

**GENERAL DESCRIPTION**

The HMC8412 is a gallium arsenide (GaAs), monolithic microwave integrated circuit (MMIC), pseudomorphic high electron mobility transistor (pHEMT), low noise wideband amplifier that operates from 0.4 GHz to 11 GHz.

The HMC8412 provides a typical gain of 15.5 dB, a 1.4 dB typical noise figure, and a typical output third-order intercept (OIP3) of ≤33 dBm, requiring only 60 mA from a 5 V drain supply voltage. The saturated output power ( $P_{SAT}$ ) of ≤20.5 dBm typical enables the low noise amplifier (LNA) to function as a local oscillator

**FUNCTIONAL BLOCK DIAGRAM***Figure 1.*

(LO) driver for many Analog Devices, Inc., balanced, inphase and quadrature (I/Q) or image rejection mixers.

The HMC8412 also features inputs and outputs that are internally matched to  $50\ \Omega$ , making the device ideal for surface-mount technology (SMT)-based, high capacity microwave radio applications.

The HMC8412 is housed in an **RoHS-compliant, 2 mm × 2 mm, 6-lead LFCSP**.

**Rev. 0**

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

**Document Feedback**

## TABLE OF CONTENTS

Features .....	1	Electrostatic Discharge (ESD) Ratings .....	5
Applications .....	1	ESD Caution .....	5
Functional Block Diagram .....	1	Pin Configuration and Function Descriptions .....	6
General Description .....	1	Interface Schematics .....	6
Revision History .....	2	Typical Performance Characteristics .....	7
Specifications .....	3	Theory of Operation .....	16
0.4 GHz to 3 GHz Frequency Range .....	3	Applications Information .....	17
3 GHz to 9 GHz Frequency Range.....	3	Recommended Bias Sequencing .....	17
9 GHz to 11 GHz Frequency Range .....	4	Outline Dimensions.....	18
Absolute Maximum Ratings .....	5	Ordering Guide .....	18
Thermal Resistance .....	5		

## REVISION HISTORY

5/2020—Revision 0: Initial Version

## SPECIFICATIONS

### 0.4 GHz TO 3 GHz FREQUENCY RANGE

$V_{DD} = 5$  V, supply current ( $I_{DQ}$ ) = 60 mA,  $R_{BIAS} = 1.47$  k $\Omega$ , and  $T_A = 25^\circ\text{C}$ , unless otherwise noted.

Table 1.

Parameter	Min	Typ	Max	Unit	Test Conditions/Comments
FREQUENCY RANGE	0.4		3	GHz	
GAIN Gain Variation over Temperature	13 0.010	15.5 0.010		dB dB/ $^\circ\text{C}$	
NOISE FIGURE		1.4		dB	
RETURN LOSS					
Input		14		dB	
Output		13		dB	
OUTPUT					
Power for 1 dB Compression (OP1dB)	15	18 20.5		dBm dBm	
P <sub>SAT</sub>		32		dBm	Measurement taken at output power ( $P_{OUT}$ ) per tone = 0 dBm
OIP3		40		dBm	Measurement taken at $P_{OUT}$ per tone = 0 dBm
Second-Order Intercept (OIP2)					
POWER ADDED EFFICIENCY (PAE)		28		%	Measured at P <sub>SAT</sub>
SUPPLY					
I <sub>DQ</sub>		60		mA	
V <sub>DD</sub>	2	5	6	V	

### 3 GHz TO 9 GHz FREQUENCY RANGE

$V_{DD} = 5$  V,  $I_{DQ} = 60$  mA,  $R_{BIAS} = 1.47$  k $\Omega$ , and  $T_A = 25^\circ\text{C}$ , unless otherwise noted.

Table 2.

Parameter	Min	Typ	Max	Unit	Test Conditions/Comments
FREQUENCY RANGE	3		9	GHz	
GAIN Gain Variation over Temperature	13 0.012	15 0.012		dB dB/ $^\circ\text{C}$	
NOISE FIGURE		1.5		dB	
RETURN LOSS					
Input		15		dB	
Output		16		dB	
OUTPUT					
OP1dB	15.5	18 20.5		dBm dBm	
P <sub>SAT</sub>		33		dBm	Measurement taken at $P_{OUT}$ per tone = 0 dBm
OIP3		41.5		dBm	Measurement taken at $P_{OUT}$ per tone = 0 dBm
OIP2					
PAE		29		%	Measured at P <sub>SAT</sub>
SUPPLY					
I <sub>DQ</sub>		60		mA	
V <sub>DD</sub>	2	5	6	V	

**9 GHz TO 11 GHz FREQUENCY RANGE**

$V_{DD} = 5$  V,  $I_{DQ} = 60$  mA,  $R_{BIAS} = 1.47$  k $\Omega$ , and  $T_A = 25^\circ\text{C}$ , unless otherwise noted.

**Table 3.**

Parameter	Min	Typ	Max	Unit	Test Conditions/Comments
FREQUENCY RANGE	9		11	GHz	
GAIN Gain Variation over Temperature	12 0.022	14		dB dB/ $^\circ\text{C}$	
NOISE FIGURE		1.8		dB	
RETURN LOSS					
Input		14		dB	
Output		10		dB	
OUTPUT					
OP1dB	11	14		dBm	
P <sub>SAT</sub>		18		dBm	Measurement taken at P <sub>OUT</sub> per tone = 0 dBm
OIP3		31		dBm	Measurement taken at P <sub>OUT</sub> per tone = 0 dBm
OIP2		49.5		dBm	
PAE		15.5		%	Measured at P <sub>SAT</sub>
SUPPLY					
I <sub>DQ</sub>		60		mA	
V <sub>DD</sub>	2	5	6	V	

## ABSOLUTE MAXIMUM RATINGS

Table 4.

Parameter	Rating
V <sub>DD</sub>	7 V
RF Input Power	25 dBm
Continuous Power Dissipation (P <sub>DISS</sub> ), T <sub>A</sub> = 85°C (Derate 9.15 mW/°C Above 85°C)	0.82 W
Temperature	
Storage Range	-65°C to +150°C
Operating Range	-40°C to +85°C
Peak Reflow (Moisture Sensitivity Level 1 (MSL1)) <sup>1</sup>	260°C
Junction Temperature to Maintain 1,000,000 Hours Mean Time to Failure (MTTF)	175°C
Nominal Junction Temperature (T <sub>A</sub> = 85°C, V <sub>DD</sub> = 5 V, I <sub>DQ</sub> = 60 mA)	117.8°C

<sup>1</sup>See the Ordering Guide for more information.

Stresses at or above those listed under Absolute Maximum Ratings may cause permanent damage to the product. This is a stress rating only; functional operation of the product at these or any other conditions above those indicated in the operational section of this specification is not implied. Operation beyond the maximum operating conditions for extended periods may affect product reliability.

## THERMAL RESISTANCE

Thermal performance is directly linked to printed circuit board (PCB) design and operating environment. Close attention to PCB thermal design is required.

$\theta_{JC}$  is the junction to case thermal resistance.

Table 5. Thermal Resistance

Package Type	$\theta_{JC}$	Unit
CP-6-12	109.3	°C/W

## ELECTROSTATIC DISCHARGE (ESD) RATINGS

The following ESD information is provided for handling of ESD-sensitive devices in an ESD protected area only.

Human body model (HBM) per ANSI/ESDA/JEDEC JS-001.

### ESD Ratings for HMC8412

Table 6. HMC8412, 6-Lead LFCSP

ESD Model	Withstand Threshold (V)	Class
HBM	±500	1B

## ESD CAUTION



**ESD (electrostatic discharge) sensitive device.** Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

## PIN CONFIGURATION AND FUNCTION DESCRIPTIONS




Figure 2. Pin Configuration

Table 7. Pin Function Descriptions

Pin No.	Mnemonic	Description
1	R <sub>BIAST</sub>	Current Mirror Bias Resistor. Use the R <sub>BIAST</sub> pin to set the quiescent current by connecting the external bias resistor as defined in Table 8. Refer to Figure 60 for the bias resistor connection. See Figure 3 for the interface schematic.
2, 5	GND	Ground. The GND pin must be connected to RF and dc ground. See Figure 6 for the interface schematic.
3	RF <sub>IN</sub>	RF Input. The RF <sub>IN</sub> pin is ac-coupled and matched to 50 Ω. See Figure 4 for the interface schematic.
4	RF <sub>OUT</sub>	RF Output. The RF <sub>OUT</sub> pin is ac-coupled and matched to 50 Ω. See Figure 5 for the interface schematic.
6	V <sub>DD</sub>	Drain Supply Voltage for the Amplifier. See Figure 5 for the interface schematic.
	EPAD	Exposed Pad. The exposed pad must be connected to the RF and dc ground.

## INTERFACE SCHEMATICS




Figure 3. R<sub>BIAST</sub> Interface Schematic




Figure 5. V<sub>DD</sub> and RF<sub>OUT</sub> Interface Schematic




Figure 4. RF<sub>IN</sub> Interface Schematic



Figure 6. GND Interface Schematic

## TYPICAL PERFORMANCE CHARACTERISTICS




Figure 7. Broadband Gain and Return Loss vs. Frequency,  
10 MHz to 20 GHz,  $V_{DD} = 5$  V,  $I_{DQ} = 60$  mA,  $R_{BIAS} = 1.47$  k $\Omega$




Figure 10. Gain vs. Frequency for Various Temperatures, 300 MHz to 1 GHz,  
 $V_{DD} = 5$  V,  $I_{DQ} = 60$  mA,  $R_{BIAS} = 1.47$  k $\Omega$




Figure 8. Gain vs. Frequency for Various Temperatures, 1 GHz to 13 GHz,  
 $V_{DD} = 5$  V,  $I_{DQ} = 60$  mA,  $R_{BIAS} = 1.47$  k $\Omega$




Figure 11. Gain vs. Frequency for Various  $V_{DD}$  and  $I_{DQ}$  Values,  
300 MHz to 13 GHz,  $R_{BIAS} = 1.47$  k $\Omega$




Figure 9. Gain vs. Frequency for Various  $R_{BIAS}$  Values and  $I_{DQ}$ ,  
300 MHz to 13 GHz,  $V_{DD} = 5$  V







Figure 12. Input Return Loss vs. Frequency for Various Temperatures,  
300 MHz to 1 GHz,  $V_{DD} = 5$  V,  $I_{DQ} = 60$  mA,  $R_{BIAS} = 1.47$  k $\Omega$




23882-013




23882-016




23882-014



23882-017



23882-015



23882-018




Figure 19. Output Return Loss vs. Frequency for Various  $R_{BIAS}$  Values and  $I_{DQ}$ , 300 MHz to 13 GHz,  $V_{DD} = 5$  V




Figure 22. Reverse Isolation vs. Frequency for Various Temperatures, 300 MHz to 13 GHz,  $V_{DD} = 5$  V,  $I_{DQ} = 60$  mA,  $R_{BIAS} = 1.47$  kΩ




Figure 20. Noise Figure vs. Frequency for Various Temperatures, 300 MHz to 1 GHz,  $V_{DD} = 5$  V,  $I_{DQ} = 60$  mA,  $R_{BIAS} = 1.47$  kΩ




Figure 23. Noise Figure vs. Frequency for Various Temperatures, 1 GHz to 13 GHz,  $V_{DD} = 5$  V,  $I_{DQ} = 60$  mA,  $R_{BIAS} = 1.47$  kΩ




Figure 21. Noise Figure vs. Frequency for Various  $V_{DD}$  and  $I_{DQ}$  Values, 300 MHz to 13 GHz,  $R_{BIAS} = 1.47$  kΩ







Figure 24. Noise Figure vs. Frequency for Various  $R_{BIAS}$  Values and  $I_{DQ}$ , 300 MHz to 13 GHz,  $V_{DD} = 5$  V




23882-025




23882-028




23882-026









23882-029



23882-027



23882-030






Figure 37. Gain, PAE,  $P_{\text{OUT}}$ , and  $I_{\text{DD}}$  vs. Input Power,  
Power Compression at 10 GHz,  $V_{\text{DD}} = 5 \text{ V}$ ,  $I_{\text{DQ}} = 60 \text{ mA}$ ,  $R_{\text{BIAS}} = 1.47 \text{ k}\Omega$




Figure 40. Gain, OP1dB,  $P_{\text{SAT}}$ , and  $I_{\text{DD}}$  vs. Supply Voltage,  
Power Compression at 1 GHz,  $R_{\text{BIAS}} = 1.47 \text{ k}\Omega$




Figure 38. Gain, OP1dB,  $P_{\text{SAT}}$ , and  $I_{\text{DD}}$  vs. Supply Voltage,  
Power Compression at 3 GHz,  $R_{\text{BIAS}} = 1.47 \text{ k}\Omega$




Figure 41. Gain, OP1dB,  $P_{\text{SAT}}$ , and  $I_{\text{DD}}$  vs. Supply Voltage,  
Power Compression at 6 GHz,  $R_{\text{BIAS}} = 1.47 \text{ k}\Omega$




Figure 39. Gain, OP1dB,  $P_{\text{SAT}}$ , and  $I_{\text{DD}}$  vs. Supply Voltage,  
Power Compression at 10 GHz,  $R_{\text{BIAS}} = 1.47 \text{ k}\Omega$




Figure 42.  $P_{\text{DISS}}$  vs. Input Power at  $T_A = 85^\circ\text{C}$ ,  
 $V_{\text{DD}} = 5 \text{ V}$ ,  $I_{\text{DQ}} = 60 \text{ mA}$ ,  $R_{\text{BIAS}} = 1.47 \text{ k}\Omega$




Figure 43. OIP3 vs. Frequency for Various Temperatures, 300 MHz to 13 GHz,  $V_{DD} = 5$  V,  $I_{DQ} = 60$  mA,  $R_{BIAS} = 1.47$  k $\Omega$ ,  $P_{OUT}$  per Tone = 0 dBm




Figure 46. OIP3 vs. Frequency for Various Temperatures, 300 MHz to 13 GHz,  $V_{DD} = 5$  V,  $I_{DQ} = 70$  mA,  $R_{BIAS} = 1$  k $\Omega$ ,  $P_{OUT}$  per Tone = 0 dBm




Figure 44. OIP3 vs. Frequency for Various  $V_{DD}$  and  $I_{DQ}$  Values, 300 MHz to 13 GHz,  $R_{BIAS} = 1.47$  k $\Omega$ ,  $P_{OUT}$  per Tone = 0 dBm




Figure 47. OIP3 vs. Frequency for Various  $R_{BIAS}$  Values and  $I_{DQ}$ , 300 MHz to 13 GHz,  $V_{DD} = 5$  V,  $P_{OUT}$  per Tone = 0 dBm




Figure 45. OIP2 vs. Frequency for Various Temperatures, 300 MHz to 13 GHz,  $V_{DD} = 5$  V,  $I_{DQ} = 60$  mA,  $R_{BIAS} = 1.47$  k $\Omega$ ,  $P_{OUT}$  per Tone = 0 dBm












Figure 48. OIP2 vs. Frequency for Various Temperatures, 300 MHz to 13 GHz,  $V_{DD} = 5$  V,  $I_{DQ} = 70$  mA,  $R_{BIAS} = 1$  k $\Omega$ ,  $P_{OUT}$  per Tone = 0 dBm







23882-055



23882-057



23882-056



23882-059

## THEORY OF OPERATION

The HMC8412 is a GaAs, MMIC, pHEMT, low noise wideband amplifier with integrated ac-coupling capacitors and a bias inductor. A simplified schematic is shown in Figure 59.

The HMC8412 has ac-coupled, single-ended input and output ports with impedances that are nominally equal to  $50\ \Omega$  over the 0.4 GHz to 11 GHz frequency range. No external matching

components are required. To adjust the drain bias current, connect an external resistor between the  $R_{BIAS}$  and  $V_{DD}$  pins.




Figure 59. Simplified Schematic

## APPLICATIONS INFORMATION

The basic connections for operating the HMC8412 over the specified frequency range are shown in Figure 60. No external biasing inductor is required, allowing the 5 V supply to be connected to the V<sub>DD</sub> pin. 0.1 μF and 100 pF power supply decoupling capacitors are recommended. The power supply decoupling capacitors shown in Figure 60 represent the configuration used to characterize and qualify the HMC8412. It is possible to reduce the number of capacitors, but this varies from system to system. It is recommended to first remove the largest capacitors that are farthest from the device when reducing the number of capacitors.

To set I<sub>DQ</sub>, connect a resistor, R1, between the R<sub>BIAS</sub> and V<sub>DD</sub> pins. A default value of 1.47 kΩ is recommended, which results in a nominal I<sub>DQ</sub> of 60 mA. Table 8 shows how the I<sub>DQ</sub> and I<sub>DD</sub> varies vs. the bias resistor value. The R<sub>BIAS</sub> pin also draws a current that varies with the value of R<sub>BIAS</sub> (see Table 8). Do not leave the R<sub>BIAS</sub> pin open.




Figure 60. Typical Application Circuit

## RECOMMENDED BIAS SEQUENCING

### **Power-Up Sequence**

To power up, follow this bias sequence:

1. Set V<sub>DD</sub> to 5 V.
2. Apply the RF signal.

### **Power-Down Sequence**

To power down, follow this bias sequence:

1. Turn off the RF signal.
2. Set V<sub>DD</sub> to 0 V.

**Table 8. Recommended Bias Resistor Values**

R <sub>BIAS</sub> (Ω)	Total Current (mA)	I <sub>DD</sub> (mA)	R <sub>BIAS</sub> Current (mA)
670	80	77.05	2.95
790	75	72.29	2.71
1000	70	67.53	2.47
1170	65	62.76	2.24
1470	60	58.04	1.96
1730	55	53.24	1.76
2100	50	48.45	1.55
2600	45	43.67	1.33
3300	40	38.89	1.11
4300	35	34.11	0.89
5900	30	29.38	0.62
8500	25	24.51	0.49
14000	20	19.69	0.31

## OUTLINE DIMENSIONS




Figure 61. 6-Lead Lead Frame Chip Scale Package [LFCSP]

2 mm × 2 mm Body and 0.85 mm Package Height

(CP-6-12)

Dimensions shown in millimeters

## ORDERING GUIDE

Model <sup>1,2</sup>	Temperature Range	MSL Rating <sup>3</sup>	Package Description <sup>4</sup>	Package Option
HMC8412LP2FE	-40°C to +85°C	MSL1	6-Lead Lead Frame Chip Scale Package [LFCSP]	CP-6-12
HMC8412LP2FETR	-40°C to +85°C	MSL1	6-Lead Lead Frame Chip Scale Package [LFCSP]	CP-6-12
EV1HMC8412LP2F			Evaluation Board	

<sup>1</sup> The HMC8412LP2FE, HMC8412LP2FETR, and EV1HMC8412LP2F are RoHS compliant parts.

<sup>2</sup> When ordering the evaluation board only, reference the model number, EV1HMC8412LP2F.

<sup>3</sup> See the Absolute Maximum Ratings section for additional information.

<sup>4</sup> The lead finish of the HMC8412LP2FE and HMC8412LP2FETR is nickel palladium gold (NiPdAu).