



# PBSS5160T

60 V, 1 A PNP low  $V_{CEsat}$  (BISS) transistor

Rev. 04 — 15 January 2010

Product data sheet

## 1. Product profile

### 1.1 General description

PNP low  $V_{CEsat}$  Breakthrough In Small Signal (BISS) transistor in a small SOT23 (TO-236AB) Surface-Mounted Device (SMD) plastic package.

NPN complement: PBSS4160T.

### 1.2 Features

- Low collector-emitter saturation voltage  $V_{CEsat}$
- High collector current capability  $I_C$  and  $I_{CM}$
- High efficiency due to less heat generation
- Reduces Printed-Circuit Board (PCB) area required
- Cost-effective replacement for medium power transistors BCP52 and BCX52

### 1.3 Applications

- Major application segments:
  - ◆ Automotive
  - ◆ Telecom infrastructure
  - ◆ Industrial
- Power management:
  - ◆ DC-to-DC conversion
  - ◆ Supply line switching
- Peripheral driver:
  - ◆ Driver in low supply voltage applications (e.g. lamps and LEDs)
  - ◆ Inductive load drivers (e.g. relays, buzzers and motors)

### 1.4 Quick reference data



Table 1. Quick reference data

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$V_{CEO}$	collector-emitter voltage	open base	-	-	-60	V
$I_C$	collector current		-	-	-1	A
$I_{CM}$	peak collector current	$t = 1 \text{ ms}$ or limited by $T_{j(\max)}$	-	-	-2	A
$R_{CEsat}$	collector-emitter saturation resistance	$I_C = -1 \text{ A}; I_B = -100 \text{ mA}$	[1]	-	220	330
						$\text{m}\Omega$

[1] Pulse test:  $t_p \leq 300 \mu\text{s}$ ;  $\delta \leq 0.02$ .

## 2. Pinning information

**Table 2. Pinning**

Pin	Description	Simplified outline	Graphic symbol
1	base		
2	emitter		
3	collector		

006aab25

## 3. Ordering information

**Table 3. Ordering information**

Type number	Package			Version
	Name	Description		
PBSS5160T	-	plastic surface-mounted package; 3 leads		SOT23

## 4. Marking

**Table 4. Marking codes**

Type number	Marking code <sup>[1]</sup>
PBSS5160T	*U6

- [1] \* = -: made in Hong Kong
- \* = p: made in Hong Kong
- \* = t: made in Malaysia
- \* = W: made in China

## 5. Limiting values

**Table 5. Limiting values**

In accordance with the Absolute Maximum Rating System (IEC 60134).


Symbol	Parameter	Conditions	Min	Max	Unit
$V_{CBO}$	collector-base voltage	open emitter	-	-80	V
$V_{CEO}$	collector-emitter voltage	open base	-	-60	V
$V_{EBO}$	emitter-base voltage	open collector	-	-5	V
$I_C$	collector current		[1]	-0.9	A
				-1	A
$I_{CM}$	peak collector current	$t = 1 \text{ ms}$ or limited by $T_{j(\max)}$	-	-2	A
$I_B$	base current		-	-300	mA
$I_{BM}$	peak base current	$t_p \leq 300 \mu\text{s}; \delta \leq 0.02$	-	-1	A

**Table 5. Limiting values ...continued**

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
$P_{tot}$	total power dissipation	$T_{amb} \leq 25^\circ C$	[1]	-	270 mW
			[2]	-	400 mW
			[1][3]	-	1.25 W
$T_j$	junction temperature		-	150	°C
$T_{amb}$	ambient temperature		-65	+150	°C
$T_{stg}$	storage temperature		-65	+150	°C

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 1 cm<sup>2</sup>.[3] Operated under pulse conditions: duty cycle  $\delta \leq 20\%$ , pulse width  $t_p \leq 10$  ms.

## 6. Thermal characteristics


**Table 6. Thermal characteristics**

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$R_{th(j-a)}$	thermal resistance from junction to ambient	in free air	[1]	-	-	K/W
			[2]	-	-	K/W
			[1][3]	-	-	K/W

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 1 cm<sup>2</sup>.

[3] Operated under pulse conditions: duty cycle  $\delta \leq 20\%$ , pulse width  $t_p \leq 10$  ms.



FR4 PCB, standard footprint

**Fig 2. Transient thermal impedance as a function of pulse duration; typical values**


## 7. Characteristics

**Table 7. Characteristics**

$T_{amb} = 25^\circ\text{C}$  unless otherwise specified.


Symbol	Parameter	Conditions	Min	Typ	Max	Unit	
$I_{CBO}$	collector-base cut-off current	$V_{CB} = -60\text{ V}; I_E = 0\text{ A}$	-	-	-100	nA	
		$V_{CB} = -60\text{ V}; I_E = 0\text{ A}; T_j = 150^\circ\text{C}$	-	-	-50	µA	
$I_{CES}$	collector-emitter cut-off current	$V_{CE} = -60\text{ V}; V_{BE} = 0\text{ V}$	-	-	-100	nA	
$I_{EBO}$	emitter-base cut-off current	$V_{EB} = -5\text{ V}; I_C = 0\text{ A}$	-	-	-100	nA	
$h_{FE}$	DC current gain	$V_{CE} = -5\text{ V}$					
		$I_C = -1\text{ mA}$	200	350	-		
		$I_C = -500\text{ mA}$	[1] 150	250	-		
		$I_C = -1\text{ A}$	[1] 100	160	-		
$V_{CEsat}$	collector-emitter saturation voltage	$I_C = -100\text{ mA}; I_B = -1\text{ mA}$	-	-110	-160	mV	
		$I_C = -500\text{ mA}; I_B = -50\text{ mA}$	-	-120	-175	mV	
		$I_C = -1\text{ A}; I_B = -100\text{ mA}$	[1]	-	-220	-330	mV
$R_{CEsat}$	collector-emitter saturation resistance	$I_C = -1\text{ A}; I_B = -100\text{ mA}$	[1]	-	220	330	mΩ
$V_{BEsat}$	base-emitter saturation voltage	$I_C = -1\text{ A}; I_B = -50\text{ mA}$	-	-0.95	-1.1	V	
$V_{BEon}$	base-emitter turn-on voltage	$V_{CE} = -5\text{ V}; I_C = -1\text{ A}$	-	-0.82	-0.9	V	
$f_T$	transition frequency	$V_{CE} = -10\text{ V}; I_C = -50\text{ mA}; f = 100\text{ MHz}$	150	220	-	MHz	
$C_c$	collector capacitance	$V_{CB} = -10\text{ V}; I_E = i_e = 0\text{ A}; f = 1\text{ MHz}$	-	9	15	pF	

[1] Pulse test:  $t_p \leq 300\text{ }\mu\text{s}; \delta \leq 0.02$ .




$V_{CE} = -5 \text{ V}$   
(1)  $T_{\text{amb}} = 100 \text{ }^{\circ}\text{C}$   
(2)  $T_{\text{amb}} = 25 \text{ }^{\circ}\text{C}$   
(3)  $T_{\text{amb}} = -55 \text{ }^{\circ}\text{C}$

**Fig 3. DC current gain as a function of collector current; typical values**




$T_{\text{amb}} = 25 \text{ }^{\circ}\text{C}$

**Fig 4. Collector current as a function of collector-emitter voltage; typical values**




$V_{CE} = -5 \text{ V}$   
(1)  $T_{\text{amb}} = -55 \text{ }^{\circ}\text{C}$   
(2)  $T_{\text{amb}} = 25 \text{ }^{\circ}\text{C}$   
(3)  $T_{\text{amb}} = 100 \text{ }^{\circ}\text{C}$

**Fig 5. Base-emitter voltage as a function of collector current; typical values**




$I_C/I_B = 20$   
(1)  $T_{\text{amb}} = -55 \text{ }^{\circ}\text{C}$   
(2)  $T_{\text{amb}} = 25 \text{ }^{\circ}\text{C}$   
(3)  $T_{\text{amb}} = 100 \text{ }^{\circ}\text{C}$

**Fig 6. Base-emitter saturation voltage as a function of collector current; typical values**




$I_C/I_B = 20$   
(1)  $T_{amb} = 100 \text{ } ^\circ\text{C}$   
(2)  $T_{amb} = 25 \text{ } ^\circ\text{C}$   
(3)  $T_{amb} = -55 \text{ } ^\circ\text{C}$

**Fig 7.** Collector-emitter saturation voltage as a function of collector current; typical values




$I_C/I_B = 10$   
(1)  $T_{amb} = 100 \text{ } ^\circ\text{C}$   
(2)  $T_{amb} = 25 \text{ } ^\circ\text{C}$   
(3)  $T_{amb} = -55 \text{ } ^\circ\text{C}$

**Fig 8.** Collector-emitter saturation voltage as a function of collector current; typical values



$T_{amb} = 25 \text{ } ^\circ\text{C}$   
(1)  $I_C/I_B = 100$   
(2)  $I_C/I_B = 50$

**Fig 9.** Collector-emitter saturation voltage as a function of collector current; typical values



$I_C/I_B = 20$   
(1)  $T_{amb} = 100 \text{ } ^\circ\text{C}$   
(2)  $T_{amb} = 25 \text{ } ^\circ\text{C}$   
(3)  $T_{amb} = -55 \text{ } ^\circ\text{C}$

**Fig 10.** Collector-emitter saturation resistance as a function of collector current; typical values

## 8. Package outline




Fig 11. Package outline SOT23 (TO-236AB)

## 9. Packing information

**Table 8. Packing methods**

The indicated -xxx are the last three digits of the 12NC ordering code.<sup>[1]</sup>

Type number	Package	Description	Packing quantity	
PBSS5160T	SOT23	4 mm pitch, 8 mm tape and reel	3000	10000

[1] For further information and the availability of packing methods, see [Section 12](#).

## 10. Revision history

**Table 9. Revision history**

Document ID	Release date	Data sheet status	Change notice	Supersedes
PBSS5160T_4	20100115	Product data sheet	-	PBSS5160T_N_3
Modifications:	<ul style="list-style-type: none"><li>The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors.</li><li>Legal texts have been adapted to the new company name where appropriate.</li><li><a href="#">Table 1 "Quick reference data"</a>: amended</li><li><a href="#">Section 4 "Marking"</a>: amended</li><li><a href="#">Figure 4</a>: updated</li><li><a href="#">Figure 11</a>: superseded by minimized package outline drawing</li><li><a href="#">Section 9 "Packing information"</a>: added</li><li><a href="#">Section 11 "Legal information"</a>: updated</li></ul>			
PBSS5160T_N_3	20080718	Product data sheet	-	PBSS5160T_2
PBSS5160T_2	20040527	Product specification	-	PBSS5160T_1
PBSS5160T_1	20030623	Product specification	-	-

## 11. Legal information

### 11.1 Data sheet status

Document status <sup>[1][2]</sup>	Product status <sup>[3]</sup>	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nexperia.com>.

### 11.2 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

### 11.3 Disclaimers

**General** — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

**Right to make changes** — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — Nexperia products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental

damage. Nexperia accepts no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Terms and conditions of sale** — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nexperia.com/profile/terms>, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by Nexperia. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

**Quick reference data** — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

### 11.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 12. Contact information

For more information, please visit: <http://www.nexperia.com>

For sales office addresses, please send an email to: [salesaddresses@nexperia.com](mailto:salesaddresses@nexperia.com)

## 13. Contents

<b>1</b>	<b>Product profile</b>	<b>1</b>
1.1	General description	1
1.2	Features	1
1.3	Applications	1
1.4	Quick reference data	1
<b>2</b>	<b>Pinning information</b>	<b>2</b>
<b>3</b>	<b>Ordering information</b>	<b>2</b>
<b>4</b>	<b>Marking</b>	<b>2</b>
<b>5</b>	<b>Limiting values</b>	<b>2</b>
<b>6</b>	<b>Thermal characteristics</b>	<b>4</b>
<b>7</b>	<b>Characteristics</b>	<b>5</b>
<b>8</b>	<b>Package outline</b>	<b>8</b>
<b>9</b>	<b>Packing information</b>	<b>8</b>
<b>10</b>	<b>Revision history</b>	<b>9</b>
<b>11</b>	<b>Legal information</b>	<b>10</b>
11.1	Data sheet status	10
11.2	Definitions	10
11.3	Disclaimers	10
11.4	Trademarks	10
<b>12</b>	<b>Contact information</b>	<b>10</b>
<b>13</b>	<b>Contents</b>	<b>11</b>